

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





LB888 3" LB FM8 Cond Body Crouse-Hinds

Catalog Number	LB888
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 8 Conduit Outlet Body, Feraloy Iron Alloy, LB Shape, 3"
Weight per unit	15.0 (lbs/each)
Product Category	Bodies & Covers

Features

dimensions 13.9400 IN X 5.0000 IN X 6.5000 IN Form 8 **Form**

Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

Dimensions and Weight

Height	6-1/2
Hub Size	3 in
Length	13-15/16
	5

Descriptions

Description	3" LB FM8 COND BODY
extra long description	CRS-H LB888 3 LB FORM 8 THRD RIGID
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 8 bodies are offered in seven different shapes to provide the most flexible offering on the market. Form 8 Condulet outlet bodies provide more room for heavier conductors. Many shapes and sizes are available for rigid threaded conduit. Two cover screws on all body sizes provide tight
Long Description	Eaton Crouse-Hinds series Condulet Form 8 conduit outlet body, Feraloy iron alloy, LB shape, 3"
Product Type	3 LB Form 8 THRD Rigid Outlet Body

Manufacturer Information

Brand	Eaton
GTIN	00782274517506
Manufacturers Part Number	LB888
UPC	782274517506



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging Carton	
Carton	1
Weight Per each	14.95
Uses, Certifications, and Standards Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other

UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D