

FEATURES & SPECIFICATIONS

INTENDED USE — LBL LED wraparound provides a digital lighting platform to deliver general ambient lighting for surface-mount applications. The LED system delivers long life and excellent color to ensure a quality, low-maintenance lighting installation. Ideal for closets, storage rooms, hallways, stairwells and offices.
CONSTRUCTION — Metal parts are die formed from pre-painted code-gauge steel. Prismatic diffuser is 100% acrylic with sonically welded luminous ends. Continuous side flanges on fixture body provide light trap and continuous diffuser support to prevent accidental opening and simplify maintenance.

OPTICS — Curved prismatic diffuser with linear side prisms and highly transmissive overlay minimizes lamp image and provides high-angle brightness control. Luminous end plates soften appearance for improved aesthetics.

ELECTRICAL — Long-life LEDs, coupled with high-efficiency drivers, provide superior quantity and quality of illumination for extended service life. 90% LED lumen maintenance at 50,000 hours (L90/50,000). The LEDs have a CRI of 82.

eldoLED driver options deliver choice of dimming range and choices for control, while assuring flicker-free, low-current inrush, 89% efficiency and low EMI.

Step-level dimming option allows system to be switched to 50% power for compliance with common energy codes while maintaining fixture appearance.

CONTROLS — Pair the LBL with the fixture mount Sensor Switch LSXR sensor for additional energy savings when the space is unoccupied. The LSXRHL sensor dims the fixture down to a low-level setting when there is no occupancy. This option is ideal for stairwells, back rooms, and closets due to the low occupancy level in those spaces.

Optional nLight® embedded controls continuously monitor system performance, allow for constant lumen management / compensation function, facilitate simple "plug-and-play" network and controls upgrading via Cat-5 cable. Ballast disconnect provided where required to comply with US and Canadian codes.

LISTINGS — CSA certified to meet U.S. and Canadian standards. Damp listed.

DesignLights Consortium® (DLC) Premium qualified product and DLC qualified product. Not all versions of this product may be DLC Premium qualified or DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

BUY AMERICAN ACT — Product with the BAA option is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS and DOT regulations. Please refer to www.acuitybrands.com/buy-american for additional information.

WARRANTY — 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Catalog Number	
Notes	·
Туре	

Low-Profile Curved-Basket LED Wraparound















****** Capable Luminaire


This item is an A+ capable luminaire, which has been designed and tested to provide consistent color appearance and out-of-the-box control compatibility with simple commissioning.

- All configurations of this luminaire meet the Acuity Brands' specification for chromatic consistency
- This luminaire is part of an A+ Certified solution for nLight® control networks when ordered with drivers marked by a shaded background*
- This luminaire is part of an A+ Certified solution for nLight control networks, providing advanced control functionality at the luminaire level, when selection includes driver and control options marked by a shaded background*

To learn more about A+, visit www.acuitybrands.com/aplus.

*See ordering tree for details

DECORATIVE RESIDENTIAL LBL4



ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: LBL4 4000LM 80CRI 35K MIN10 GZT MVOLT

LBL4						
Series	Lumens ¹	CRI	Color temperature	Minimum Dimming Level	Dimming	Voltage
LBL4 4' LED wrap	3000LM 3000 lumens 4000LM 4000 lumens 4800LM 4800 lumens 6000LM 6000 lumens 7200LM 7200 lumens	80CRI 80 CRI	30K 3000 K 35K 3500 K 40K 4000 K 50K 5000 K	MIN10 Dims to 10%² MIN1 Dims to 1%³ NODIM On/off, non-dimming⁴ SLD Step-level dimming⁴	(blank) None 13 GZT Generic 0-10V Dimming ZT eldoLED 0-10V dimming	MVOLT 120-277V 347 347V 5.14

			Occupancy Sensor	
Emergency Options 14	Control Input/ Lumen Management Options 13	Occupancy Control Options	Technology Option	Options
EL7L 700 nominal lumen battery pack (Noncompliant with CA T20)6 EL14L 1400 nominal lumen battery pack (Noncompliant with CA T20)6 E10WLCP EM Self-Diagnostic battery pack, 10W Constant Power, Certified in CA Title 20 MAEDBS6 EMG for use with nLight on generator supply EM power?	NLIGHT nLight enabled CL80 NLIGHT nLight enabled, Constant lumen output, 80%	LSXRHL Sensor Switch® fixture mount sensor with High/Low occupancy operation ^{8,9} LSXR10 Sensor Switch® fixture mount sensor with on/off occupancy operation ⁸	PIR Passive Infrared ¹¹	GLR Fast-blowing fuse ¹² GMF Slow-blowing fuse ¹² BAA Buy America(n) Act Compliant BDP Factory Installed Ballast Disconnect Plug

ORDERING INFORMATION

Catalog number	UPC	Description	Lumens	Color temperature	Lens type	Voltage	Wattage ²	Pallet qty	Standard carton qty.
LBL4 LP835 ¹⁰	190887819199	4' LED Wraparound	4,188	3500 K	Patterned #12 acrylic	120-277	32	56	1
LBL4 LP840 ¹⁰	190887819359	4' LED Wraparound	4,253	4000 K	Patterned #12 acrylic	120-277	32	56	1
LBL4 347 LP835	190887856682	4' LED Wraparound	4,188	3500 K	Patterned #12 acrylic	347	34.5	56	1
LBL4 347 LP840	190887856705	4' LED Wraparound	4,253	4000 K	Patterned #12 acrylic	347	34.5	56	1

Replacement Part

Fixture: LBL4 & Contractor Select

Description: LBL 4' DIFFUSER

Part Number: DLBL48

Notes

- 1 Approximate lumen output.
- 2 Requires GZT control option.
- 3 Requires GZT, ZT, or NLIGHT control.
- 4 Not available with Control or Sensor Options.
- 5 Not available with SLD option.
- 6 Not available with 7200LM option.
- 7 nLight EMG option requires a conection to existing nLight network. Power is provided from a separate N80 or N100 enabled fixture. Requires NLIGHT.
- 8 Requires MIN1, ZT and PIR options.
- 9 Dims to approximately 10% light output when unoccupied.
- 10 Product in stock.
- 11 Only available with Occupany Control option.
- 12 Must specify voltage. 120 or 277, with GLR and GMF fusing.
- 13 When Control Input/ Lumen Management option specified leave Dimming section blank.
- 14 347 not available with battery option

Performance Data								
Lumen Package	Lumens	Input Watts	LPW					
3000LM 80CRI 30K	3167	25.6	124					
3000LM 80CRI 35K	3237	25.6	127					
3000LM 80CRI 40K	3288	25.6	129					
3000LM 80CRI 50K	3409	25.6	133					
4000LM 80CRI 30K	4097	32.4	126					
4000LM 80CRI 35K	4188	32.4	129					
4000LM 80CRI 40K	4253	32.4	131					
4000LM 80CRI 50K	4410	32.4	136					
4800LM 80CRI 30K	4695	40.5	116					
4800LM 80CRI 35K	4799	40.5	119					
4800LM 80CRI 40K	4874	40.5	120					
4800LM 80CRI 50K	5053	40.5	125					
6000LM 80CRI 30K	5968	49.7	120					
6000LM 80CRI 35K	6101	49.7	123					
6000LM 80CRI 40K	6196	49.7	125					
6000LM 80CRI 50K	6424	49.7	129					
7200LM 80CRI 30K	7066	62.0	114					
7200LM 80CRI 35K	7224	62.0	117					
7200LM 80CRI 40K	7336	62.0	118					
7200LM 80CRI 50K	7606	62.0	123					



Sensor Switch LSXRHL Sensor

Lens type: 10 - Low Mount 360° coverage

Dimming: HL - High/Low Occupancy operation

Min Dim Level: 3V - approximately 10% light output when unoccupied

Time Delay: 5M - 5 minutes

How to Estimate Delivered Lumens in Emergency Mode


Use the formula below to estimate the delivered lumens in emergency mode.

Delivered Lumens = 1.25 x P x LPW

P=0 uput power of emergency driver. P=10W for E10WLCP option. $LPW=Lumen\ per\ watt\ rating\ of\ the\ luminaire.\ LPW\ information\ available\ in\ Performance\ Data\ section.$

PHOTOMETRICS

LBL4 4800LM 80CRI 35K



Coefficients of Utilization

10% 105 86
105
86
73
62
54
47
42
37
34
30
28

Zonal Lumen Summary

			. ,
Zone	Lumens	% Lamp	% Fixture
0° - 30°	1400	29.2	29.2
0° - 40°	2229	46.4	46.4
0° - 60°	3509	73.1	73.1
0° - 90°	4250	88.6	88.6
90° - 120°	266	5.5	5.5
90° - 130°	348	7.3	7.3
90° - 150°	478	10.0	10.0
90° - 180°	549	11.4	11.4
0° - 180°	4799	100.0	100.0

CP Summary

90

1823

1828

1776

1640

1384

1020

693

464

343

233

177

0°

1823

1813

1744

1594

1332

958

576

302

177

58

5

MOUNTING DATA

Aircraft Cable

 ${\it STACG-the\, standard\, aircraft\, cable\, kit\, in\, which\, only\, the\, hanging\, wire\, will\, be\, included.}$

STACGF — will include a power feed cable with 3 conductors (HOT, NEUTRAL, GROUND)

STACGFD – same as above with Dimming leads (HOT, NEUTRAL, GROUND, VIOLET, GREY)

STACGE — will include a power feed cable with 4 conductors (HOT1, HOT2, NEUTRAL, GROUND) for fixtures with a battery pack.

Ceiling Type

F1 – for use with most T-bar and screw slot grid ceiling applications. Designed for on-grid and off-grid installations.

F2 – for use with recessed or surface-mount horizontal J-box applications.


How to order:

- For aircraft cable, choose one STACG, STACGF, STACGFD, or STACGE (required for each suspension point)
- 2. Choose length 36", 72" or 144"
- 3. For ceiling type choose F1 or F2
- Ex. STACG36 F1, STACGF72 F2

Stem Suspension

 $Individual\ installation --- Two\ single-stem\ hangers\ required$





Note: 2' configurations with emergency option cannot be stem mounted.

DIMENSIONS

Specifications

Length: 48 (122.0)

Width: 10 (25.4)

Depth: 2-3/4 (7.0)

10
(25.4)

(7.0)

All dimensions are inches (centimeters) unless otherwise indicated.



FEATURES & SPECIFICATIONS

INTENDED USE — LBL LED wraparound provides a digital lighting platform to deliver general ambient lighting for surface-mount applications. The LED system delivers long life and excellent color to ensure a quality, low-maintenance lighting installation. Ideal for closets, storage rooms, hallways, stairwells and offices.
CONSTRUCTION — Metal parts are die formed from pre-painted code-gauge steel. Prismatic diffuser is 100% acrylic with sonically welded luminous ends. Continuous side flanges on fixture body provide light trap and continuous diffuser support to prevent accidental opening and simplify maintenance.

OPTICS — Curved prismatic diffuser with linear side prisms and highly transmissive overlay minimizes lamp image and provides high-angle brightness control. Luminous end plates soften appearance for improved aesthetics.

ELECTRICAL — Long-life LEDs, coupled with high-efficiency drivers, provide superior quantity and quality of illumination for extended service life. 90% LED lumen maintenance at 50,000 hours (L90/50,000). The LEDs have a CRI of 82.

eldoLED driver options deliver choice of dimming range and choices for control, while assuring flicker-free, low-current inrush, 89% efficiency and low EMI.

Step-level dimming option allows system to be switched to 50% power for compliance with common energy codes while maintaining fixture appearance.

CONTROLS — Pair the LBL with the fixture mount Sensor Switch LSXR sensor for additional energy savings when the space is unoccupied. The LSXRHL sensor dims the fixture down to a low-level setting when there is no occupancy. This option is ideal for stairwells, back rooms, and closets due to the low occupancy level in those spaces.

Optional nLight® embedded controls continuously monitor system performance, allow for constant lumen management / compensation function, facilitate simple "plug-and-play" network and controls upgrading via Cat-5 cable. Ballast disconnect provided where required to comply with US and Canadian codes.

LISTINGS — CSA certified to meet U.S. and Canadian standards. Damp listed.

DesignLights Consortium® (DLC) Premium qualified product and DLC qualified product. Not all versions of this product may be DLC Premium qualified or DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

BUY AMERICAN ACT — Product with the BAA option is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS and DOT regulations. Please refer to www.acuitybrands.com/buy-american for additional information.

WARRANTY — 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Catalog Number	
Notes	·
Туре	

Low-Profile Curved-Basket LED Wraparound















****** Capable Luminaire


This item is an A+ capable luminaire, which has been designed and tested to provide consistent color appearance and out-of-the-box control compatibility with simple commissioning.

- All configurations of this luminaire meet the Acuity Brands' specification for chromatic consistency
- This luminaire is part of an A+ Certified solution for nLight® control networks when ordered with drivers marked by a shaded background*
- This luminaire is part of an A+ Certified solution for nLight control networks, providing advanced control functionality at the luminaire level, when selection includes driver and control options marked by a shaded background*

To learn more about A+, visit www.acuitybrands.com/aplus.

*See ordering tree for details

DECORATIVE RESIDENTIAL LBL4



ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: LBL4 4000LM 80CRI 35K MIN10 GZT MVOLT

LBL4						
Series	Lumens ¹	CRI	Color temperature	Minimum Dimming Level	Dimming	Voltage
LBL4 4' LED wrap	3000LM 3000 lumens 4000LM 4000 lumens 4800LM 4800 lumens 6000LM 6000 lumens 7200LM 7200 lumens	80CRI 80 CRI	30K 3000 K 35K 3500 K 40K 4000 K 50K 5000 K	MIN10 Dims to 10%² MIN1 Dims to 1%³ NODIM On/off, non-dimming⁴ SLD Step-level dimming⁴	(blank) None 13 GZT Generic 0-10V Dimming ZT eldoLED 0-10V dimming	MVOLT 120-277V 347 347V 5.14

			Occupancy Sensor	
Emergency Options 14	Control Input/ Lumen Management Options 13	Occupancy Control Options	Technology Option	Options
EL7L 700 nominal lumen battery pack (Noncompliant with CA T20)6 EL14L 1400 nominal lumen battery pack (Noncompliant with CA T20)6 E10WLCP EM Self-Diagnostic battery pack, 10W Constant Power, Certified in CA Title 20 MAEDBS6 EMG for use with nLight on generator supply EM power?	NLIGHT nLight enabled CL80 NLIGHT nLight enabled, Constant lumen output, 80%	LSXRHL Sensor Switch® fixture mount sensor with High/Low occupancy operation ^{8,9} LSXR10 Sensor Switch® fixture mount sensor with on/off occupancy operation ⁸	PIR Passive Infrared ¹¹	GLR Fast-blowing fuse ¹² GMF Slow-blowing fuse ¹² BAA Buy America(n) Act Compliant BDP Factory Installed Ballast Disconnect Plug

ORDERING INFORMATION

Catalog number	UPC	Description	Lumens	Color temperature	Lens type	Voltage	Wattage ²	Pallet qty	Standard carton qty.
LBL4 LP835 ¹⁰	190887819199	4' LED Wraparound	4,188	3500 K	Patterned #12 acrylic	120-277	32	56	1
LBL4 LP840 ¹⁰	190887819359	4' LED Wraparound	4,253	4000 K	Patterned #12 acrylic	120-277	32	56	1
LBL4 347 LP835	190887856682	4' LED Wraparound	4,188	3500 K	Patterned #12 acrylic	347	34.5	56	1
LBL4 347 LP840	190887856705	4' LED Wraparound	4,253	4000 K	Patterned #12 acrylic	347	34.5	56	1

Replacement Part

Fixture: LBL4 & Contractor Select

Description: LBL 4' DIFFUSER

Part Number: DLBL48

Notes

- 1 Approximate lumen output.
- 2 Requires GZT control option.
- 3 Requires GZT, ZT, or NLIGHT control.
- 4 Not available with Control or Sensor Options.
- 5 Not available with SLD option.
- 6 Not available with 7200LM option.
- 7 nLight EMG option requires a conection to existing nLight network. Power is provided from a separate N80 or N100 enabled fixture. Requires NLIGHT.
- 8 Requires MIN1, ZT and PIR options.
- 9 Dims to approximately 10% light output when unoccupied.
- 10 Product in stock.
- 11 Only available with Occupany Control option.
- 12 Must specify voltage. 120 or 277, with GLR and GMF fusing.
- 13 When Control Input/ Lumen Management option specified leave Dimming section blank.
- 14 347 not available with battery option

Performance Data								
Lumen Package	Lumens	Input Watts	LPW					
3000LM 80CRI 30K	3167	25.6	124					
3000LM 80CRI 35K	3237	25.6	127					
3000LM 80CRI 40K	3288	25.6	129					
3000LM 80CRI 50K	3409	25.6	133					
4000LM 80CRI 30K	4097	32.4	126					
4000LM 80CRI 35K	4188	32.4	129					
4000LM 80CRI 40K	4253	32.4	131					
4000LM 80CRI 50K	4410	32.4	136					
4800LM 80CRI 30K	4695	40.5	116					
4800LM 80CRI 35K	4799	40.5	119					
4800LM 80CRI 40K	4874	40.5	120					
4800LM 80CRI 50K	5053	40.5	125					
6000LM 80CRI 30K	5968	49.7	120					
6000LM 80CRI 35K	6101	49.7	123					
6000LM 80CRI 40K	6196	49.7	125					
6000LM 80CRI 50K	6424	49.7	129					
7200LM 80CRI 30K	7066	62.0	114					
7200LM 80CRI 35K	7224	62.0	117					
7200LM 80CRI 40K	7336	62.0	118					
7200LM 80CRI 50K	7606	62.0	123					



Sensor Switch LSXRHL Sensor

Lens type: 10 - Low Mount 360° coverage

Dimming: HL - High/Low Occupancy operation

Min Dim Level: 3V - approximately 10% light output when unoccupied

Time Delay: 5M - 5 minutes

How to Estimate Delivered Lumens in Emergency Mode


Use the formula below to estimate the delivered lumens in emergency mode.

Delivered Lumens = 1.25 x P x LPW

P=0 uput power of emergency driver. P=10W for E10WLCP option. $LPW=Lumen\ per\ watt\ rating\ of\ the\ luminaire.\ LPW\ information\ available\ in\ Performance\ Data\ section.$

PHOTOMETRICS

LBL4 4800LM 80CRI 35K



Coefficients of Utilization

pt				2	0%				
рс	80%			70%			50%		
pw	70%50%30%			50%30%10%			50%30%10%		
0	116	116	116	112	112	112	105	105	105
1	106	102	98	98	95	91	92	89	86
2	97	90	83	87	81	76	81	77	73
3	89	80	72	77	70	65	73	67	62
4 م	82	71	63	69	61	56	65	59	54
~ 2	76	64	56	62	54	49	59	52	47
^щ 6	71	58	50	56	49	43	54	47	42
7	66	53	45	52	44	38	49	42	37
8	61	48	40	47	40	34	45	38	34
9	57	45	37	44	36	31	42	35	30
10	54	41	34	40	33	28	39	32	28

Zonal Lumen Summary

			. ,
Zone	Lumens	% Lamp	% Fixture
0° - 30°	1400	29.2	29.2
0° - 40°	2229	46.4	46.4
0° - 60°	3509	73.1	73.1
0° - 90°	4250	88.6	88.6
90° - 120°	266	5.5	5.5
90° - 130°	348	7.3	7.3
90° - 150°	478	10.0	10.0
90° - 180°	549	11.4	11.4
0° - 180°	4799	100.0	100.0

CP Summary

90

1823

1828

1776

1640

1384

1020

693

464

343

233

177

0°

1823

1813

1744

1594

1332

958

576

302

177

58

5

MOUNTING DATA

Aircraft Cable

 ${\it STACG-the\, standard\, aircraft\, cable\, kit\, in\, which\, only\, the\, hanging\, wire\, will\, be\, included.}$

STACGF — will include a power feed cable with 3 conductors (HOT, NEUTRAL, GROUND)

STACGFD – same as above with Dimming leads (HOT, NEUTRAL, GROUND, VIOLET, GREY)

STACGE — will include a power feed cable with 4 conductors (HOT1, HOT2, NEUTRAL, GROUND) for fixtures with a battery pack.

Ceiling Type

F1 – for use with most T-bar and screw slot grid ceiling applications. Designed for on-grid and off-grid installations.

F2 – for use with recessed or surface-mount horizontal J-box applications.


How to order:

- For aircraft cable, choose one STACG, STACGF, STACGFD, or STACGE (required for each suspension point)
- 2. Choose length 36", 72" or 144"
- 3. For ceiling type choose F1 or F2
- Ex. STACG36 F1, STACGF72 F2

Stem Suspension

 $Individual\ installation --- Two\ single-stem\ hangers\ required$





Note: 2' configurations with emergency option cannot be stem mounted.

DIMENSIONS

Specifications

Length: 48 (122.0)

Width: 10 (25.4)

Depth: 2-3/4 (7.0)

10
(25.4)

(7.0)

All dimensions are inches (centimeters) unless otherwise indicated.