



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



LBY45 1-1/4" 90D Conduit Elbow *Crouse-Hinds*

| | |
|------------------|--|
| Catalog Number | LBY45 |
| Manufacturer | Crouse-Hinds |
| Description | Service Entrance Elbow, 1-1/4 In Trade Size, Lby Model, Electro Galvanized and Aluminum Acrylic Paint, 2.6 LB/Ea |
| Weight per unit | 2.6 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |

Features

| | |
|------------|-----------------------------------|
| connection | Threaded |
| dimensions | 2.9400 IN X 2.9400 IN X 3.7800 IN |

Material, Color, and Finish

| | |
|--------|---|
| Finish | Electrogalvanized With Aluminum Acrylic Painted |
|--------|---|

Descriptions

| | |
|------------------------|--|
| Description | 1-1/4" 90D CONDUIT ELBOW |
| extra long description | CRS-H LBY45 1 1/4 LBY ELBOW CVR |
| Features | Crouse-Hinds series explosionproof unions are installed in rigid/IMC conduit systems to connect conduit to conduit, a conduit fitting, junction box or device enclosure. Expansion unions are also available, which allow for expansion and contraction of conduit and compensate for conduit cut too short. Available in a variety of materials, including stainless steel, to suit customer preferences. Explosionproof elbows allow for a 90° change in direction to the conduit run, or when terminating at a box or fit |

Manufacturer Information

| | |
|-------|----------------|
| Brand | Eaton |
| GTIN | 00782274521350 |
| UPC | 782274521350 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-----------------------------|
| Category Description | HAZARDOUS LOCATION FITTINGS |
| Type | ELBOW |

Packaging

| | |
|-----------------|-----|
| Carton | 1 |
| Package | 2 |
| Weight Per each | 2.6 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Enclosure

Class I Div 1 2 Group C D, Class II Div 1 Group E F G, Class II Div 2
Group F G, Class III

standard

UL 886, CSA C22.2