



LCCX814AL 2-HL LNG Flex Lug

Panduit Corporation

Catalog Number	LCCX814AL
Manufacturer	Panduit Corporation
Description	The LCCX8-14A-L Tin-Plated Copper Compression Lug, Two-Hole, Long Barrel, Has Color-Coded Barrels Marked With Panduit and Specified Competitor Die Index Numbers For Proper Crimp Die Selection. The Long Barrel Maximizes The Number Of Crimps and Provides Premium Wire Pull-Out Strength and Performance. The Generously Beveled Wire Entry Prevents Bent Back Strands When Inserting The Conductor Into The Barrel. UL Listed and CSA Certified.
Weight per unit	1.0 (lbs/each)
Product Category	Large Terminals & Connectors

Features

Material	Tin-Plated Copper
media	Yes
Number of Holes	2
Stud Size	1/4

Material, Color, and Finish

Color	Red
-------	-----

Dimensions and Weight

Size	#8 AWG Class B, C, G, H, I, K, M and DLO
------	--

Descriptions

Description	2-HL LNG FLEX LUG
extra long description	PAN LCCX8-14A-L Pan-Lug™ LCCX8-14A-
Long Description	The LCCX8-14A-L Tin-Plated Copper Compression Lug, two-hole, long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands when inserting the conductor into the barrel. UL Listed and CSA Certified.

Product Type	Pan-Lug™ LCCX8-14A-L Tin PLT Copper, STRT, Two 1/4" Stud, PK
Special Features	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	PANDUIT
GTIN	00074983425266
Manufacturers Part Number	LCCX8-14A-L
UPC	074983425266

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
----------------------	-----------------------------------

Packaging

Carton	1
Package	50
Weight Per each	1.0499

Uses, Certifications, and Standards

Mounting standard	3/4 CSA certified C22.2 No. 65-13, UL Listed to 486A-486B File #E52164, ABS approved
-------------------	---