

InvisiLED® Pro


24V LED Tape Light

WAC LIGHTING

Responsible Lighting®



Tape Section



3 LED "L" Connector

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Professional grade white tape light that delivers optimal color consistency and brightness. An ideal system for task or accent lighting applications.

FEATURES

- Both sides of field cut material can be used with male to male adapter
- Ultra thin profile at 3/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 2" at the end of a run
- Three mounting methods provided for different surfaces
- Specially rated for installation in the storage area of a clothes closet
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Length	Qty	Tape Color
LED-T24	3	W 2700K	85	200	2IN 2 inches	1	WT White
		P 3000K	85	200	2IN-10 2 inches	10	
		35 3500K	85	207	1 1 foot	1	
		C 4500K	85	215	1-40 1 foot	40	
					5 5 feet	1	

LED-T24 - -WT

Example: LED-T24P-2IN-10-WT

ORDER NUMBER – 3 LED "L" CONNECTOR



Model	Watts	Color Temp	CRI	Lumens	Tape Color
LED-T24	1.2	W 2700K	85	50	3L-WT White
		P 3000K	85	50	
		35 3500K	85	52	
		C 4500K	85	54	

LED-T24 -3L-WT

Example: LED-T24C-3L-WT

Class 2 Power Supply (Required)

Type	Model	Input	Output	Max Run	Dim	
Remote		EN-2460-RB2-T	120VAC	24VAC / 60W	20 feet	ELV
		EN-24100-RB2-T	120VAC	24VAC / 96W	33 feet	ELV
Plug-in		EN-2460-P-AR-T	120VAC	24VAC / 60W	20 feet	ELV
		EN-24100-P-AR-T	120VAC	24VAC / 96W	33 feet	ELV
Remote 277V		EN-24100-277-RB2-T	120-277VAC	24VDC / 96W	33 feet	0-10V



waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

InvisiLED® Pro

24V LED Tape Light

WAC LIGHTING

Responsible Lighting®

Indoor Controller

	Touch Panel and Motion Sensor	CT-6A-R2	Pro, Pro2, Pro3, LITE, Classic Palette
Includes a Touch Panel, an Occupancy Sensor, and a Controller AC/DC input at 12V(60W Max) or 24V(96W Max) Connect on secondary side of driver/transformer			

Indoor Electrical Accessories

	In Wall Rated Extension Cable <i>Extends distance between a hard wired power supply or a wiring box to a tape section.</i>	LED-TC-WEXT-144 LED-TC-WEXT-144-WT LED-TC-WEXT-240 LED-TC-WEXT-240-WT	Black 12 ft White 12 ft Black 20 ft White 20 ft
	In Wall Rated Joiner Cable <i>Connects tape sections. 2 female ends. 1 male to male connector included</i>	LED-TC-WIC-144 LED-TC-WIC-144-WT LED-TC-WIC-240 LED-TC-WIC-240-WT	Black 12 ft White 12 ft Black 20 ft White 20 ft
	Lead Wire <i>Alternative lengths for plug-in power supplies</i>	LED-TC-P-2 LED-TC-P-2-WT LED-TC-P-12 LED-TC-P-12-WT	Black 2 ft White 2 ft Black 12 ft White 12 ft
	Extension Cable <i>Extends distance between a hard wired power supply or a wiring box to a tape section</i>	LED-TC-EXT-144 LED-TC-EXT-144-WT	Black 12 ft White 12 ft
	Low Voltage Wiring Box With Feed <i>Neatly houses connectors for up to two wires with 12" female feed</i>	LED-TC-B-2 LED-TC-B-2-WT	Black L: 1½ in White W: ¾ in H: 7⁄8 in
	Low Voltage Wiring Box <i>Neatly houses connections for up to two wires</i>	LED-T-B	L: 1½ in W: ¾ in H: 7⁄8 in
	Wiring Box With Switch <i>Use when spanning a large gap in a system layout without leaving exposed wiring. Optional switch included</i>	TB-S	L: 6¼ in W: 1½ in H: 1¼ in

Compatible with Pro, Pro2, Pro3, LITE, Classic

	Joiner Cable	LED-TC-IC2 LED-TC-IC2-WT LED-TC-IC6 LED-TC-IC6-WT LED-TC-IC12 LED-TC-IC12-WT LED-TC-IC36 LED-TC-IC36-WT LED-TC-IC72 LED-TC-IC72-WT	Black 2 in White 2 in Black 6 in White 6 in Black 12 in White 12 in Black 36 in White 36 in Black 72 in White 72 in
	Male to male connector	LED-TC-MM	Black 50 Qty

Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette. Change directionality of tape runs and reuse cut ends of tape.

	3-Way "Y" Connector <i>Connects tape sections</i>	LED-TC-Y LED-TC-Y-WT	Black White
	4-Way "X" Connector <i>Connects tape sections</i>	LED-TC-X LED-TC-X-WT	Black White
	"L" Connector <i>Connects tape sections</i>	LED-TC-L LED-TC-L-WT	Black White
	End cap <i>1 cut and 1 male end cap</i>	LED-TC-EC LED-TC-EC-WT	Black White


Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette

InvisiLED® Pro

Indoor Aluminum Channels

WAC LIGHTING

Responsible Lighting®



Aluminum Channel
Additional End Caps

LED-T-CH
LED-T-CH-EC

5 feet
2 pcs

Diffuses light from InvisiLED tape
Includes a diffuser, two end caps, and five screws
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette




Deep Aluminum Channel
Additional End Cap

LED-T-CH1
LED-T-CH1-EC

5 feet
2 pcs

Eliminates visible hot spots
Includes a diffuser, two end caps, and five screws
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette




45° Angled Aluminum Channel
Additional End Caps

LED-T-CH2
LED-T-CH2-EC

5 feet
2 pcs

Includes a diffuser, two end caps, and ten screws
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette



Fixed Angle
Channel Clip

LED-T-CL3-PT




Adjustable
Channel
Clip

LED-T-CL2-PT

Includes 2 pieces, 4 screws. Use to mount Aluminum Channel,
Deep Aluminum Channel, 45° Angled Aluminum Channel

INDOOR MOUNTING ACCESSORIES



Aluminum Retrofit Channel

LED-T-RC 3 feet

Can be bent to create fixed curves or used as a glare shield
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette



Clear Channel

LED-T024-CH5

5 feet

Includes a diffuser, two end caps, and five screws
Provides a clean mounting surface for 3M adhesive



Clip
For surfaces that are
difficult to adhere

LED-T-CL 10 pcs
10 Screws



Curve Clip
Secures on one edge

LED-T-CL1 10 pcs
10 Screws

Clips to hold indoor InvisiLED tapes sections
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette

InvisiLED® Pro


24V LED Tape Light

WAC LIGHTING

Responsible Lighting®



Tape Section



3 LED "L" Connector

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Professional grade white tape light that delivers optimal color consistency and brightness. An ideal system for task or accent lighting applications.

FEATURES

- Both sides of field cut material can be used with male to male adapter
- Ultra thin profile at 3/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 2" at the end of a run
- Three mounting methods provided for different surfaces
- Specially rated for installation in the storage area of a clothes closet
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Length	Qty	Tape Color
LED-T24	3	W 2700K	85	200	2IN 2 inches	1	WT White
		P 3000K	85	200	2IN-10 2 inches	10	
		35 3500K	85	207	1 1 foot	1	
		C 4500K	85	215	1-40 1 foot	40	
					5 5 feet	1	

LED-T24 - -WT

Example: LED-T24P-2IN-10-WT

ORDER NUMBER – 3 LED "L" CONNECTOR



Model	Watts	Color Temp	CRI	Lumens	Tape Color
LED-T24	1.2	W 2700K	85	50	3L-WT White
		P 3000K	85	50	
		35 3500K	85	52	
		C 4500K	85	54	

LED-T24 -3L-WT

Example: LED-T24C-3L-WT

Class 2 Power Supply (Required)

Type	Model	Input	Output	Max Run	Dim	
Remote		EN-2460-RB2-T	120VAC	24VAC / 60W	20 feet	ELV
		EN-24100-RB2-T	120VAC	24VAC / 96W	33 feet	ELV
Plug-in		EN-2460-P-AR-T	120VAC	24VAC / 60W	20 feet	ELV
		EN-24100-P-AR-T	120VAC	24VAC / 96W	33 feet	ELV
Remote 277V		EN-24100-277-RB2-T	120-277VAC	24VDC / 96W	33 feet	0-10V



wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

InvisiLED® Pro

24V LED Tape Light

WAC LIGHTING

Responsible Lighting®

Indoor Controller

	Touch Panel and Motion Sensor	CT-6A-R2	<i>Pro, Pro2, Pro3, LITE, Classic Palette</i>
<i>Includes a Touch Panel, an Occupancy Sensor, and a Controller AC/DC input at 12V(60W Max) or 24V(96W Max) Connect on secondary side of driver/transformer</i>			

Indoor Electrical Accessories

	In Wall Rated Extension Cable <i>Extends distance between a hard wired power supply or a wiring box to a tape section.</i>	LED-TC-WEXT-144 LED-TC-WEXT-144-WT LED-TC-WEXT-240 LED-TC-WEXT-240-WT	<i>Black 12 ft</i> <i>White 12 ft</i> <i>Black 20 ft</i> <i>White 20 ft</i>
	In Wall Rated Joiner Cable <i>Connects tape sections. 2 female ends. 1 male to male connector included</i>	LED-TC-WIC-144 LED-TC-WIC-144-WT LED-TC-WIC-240 LED-TC-WIC-240-WT	<i>Black 12 ft</i> <i>White 12 ft</i> <i>Black 20 ft</i> <i>White 20 ft</i>
	Lead Wire <i>Alternative lengths for plug-in power supplies</i>	LED-TC-P-2 LED-TC-P-2-WT LED-TC-P-12 LED-TC-P-12-WT	<i>Black 2 ft</i> <i>White 2 ft</i> <i>Black 12 ft</i> <i>White 12 ft</i>
	Extension Cable <i>Extends distance between a hard wired power supply or a wiring box to a tape section</i>	LED-TC-EXT-144 LED-TC-EXT-144-WT	<i>Black 12 ft</i> <i>White 12 ft</i>
	Low Voltage Wiring Box With Feed <i>Neatly houses connectors for up to two wires with 12" female feed</i>	LED-TC-B-2 LED-TC-B-2-WT	<i>Black L: 1½ in</i> <i>White W: ¾ in</i> <i>H: 7⁄8 in</i>
	Low Voltage Wiring Box <i>Neatly houses connections for up to two wires</i>	LED-T-B	<i>L: 1½ in</i> <i>W: ¾ in</i> <i>H: 7⁄8 in</i>
	Wiring Box With Switch <i>Use when spanning a large gap in a system layout without leaving exposed wiring. Optional switch included</i>	TB-S	<i>L: 6¼ in</i> <i>W: 1½ in</i> <i>H: 1¼ in</i>

Compatible with Pro, Pro2, Pro3, LITE, Classic

	Joiner Cable <i>Connects tape sections</i>	LED-TC-IC2 LED-TC-IC2-WT LED-TC-IC6 LED-TC-IC6-WT LED-TC-IC12 LED-TC-IC12-WT LED-TC-IC36 LED-TC-IC36-WT LED-TC-IC72 LED-TC-IC72-WT	<i>Black 2 in</i> <i>White 2 in</i> <i>Black 6 in</i> <i>White 6 in</i> <i>Black 12 in</i> <i>White 12 in</i> <i>Black 36 in</i> <i>White 36 in</i> <i>Black 72 in</i> <i>White 72 in</i>
	Male to male connector	LED-TC-MM	<i>Black 50 Qty</i>

Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette. Change directionality of tape runs and reuse cut ends of tape.

	3-Way "Y" Connector <i>Connects tape sections</i>	LED-TC-Y LED-TC-Y-WT	<i>Black</i> <i>White</i>
	4-Way "X" Connector <i>Connects tape sections</i>	LED-TC-X LED-TC-X-WT	<i>Black</i> <i>White</i>
	"L" Connector <i>Connects tape sections</i>	LED-TC-L LED-TC-L-WT	<i>Black</i> <i>White</i>
	End cap <i>1 cut and 1 male end cap</i>	LED-TC-EC LED-TC-EC-WT	<i>Black</i> <i>White</i>


Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette

InvisiLED® Pro

Indoor Aluminum Channels

WAC LIGHTING

Responsible Lighting®



Aluminum Channel
Additional End Caps

LED-T-CH
LED-T-CH-EC

5 feet
2 pcs

*Diffuses light from InvisiLED tape
Includes a diffuser, two end caps, and five screws
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette*




Deep Aluminum Channel
Additional End Cap

LED-T-CH1
LED-T-CH1-EC

5 feet
2 pcs

*Eliminates visible hot spots
Includes a diffuser, two end caps, and five screws
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette*




45° Angled Aluminum Channel
Additional End Caps

LED-T-CH2
LED-T-CH2-EC

5 feet
2 pcs

*Includes a diffuser, two end caps, and ten screws
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette*



Fixed Angle
Channel Clip

LED-T-CL3-PT




Adjustable
Channel
Clip

LED-T-CL2-PT

*Includes 2 pieces, 4 screws. Use to mount Aluminum Channel,
Deep Aluminum Channel, 45° Angled Aluminum Channel*

INDOOR MOUNTING ACCESSORIES



Aluminum Retrofit Channel

LED-T-RC 3 feet

*Can be bent to create fixed curves or used as a glare shield
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette*



Clear Channel

LED-TO24-CH5

5 feet

*Includes a diffuser, two end caps, and five screws
Provides a clean mounting surface for 3M adhesive*



Clip
For surfaces that are
difficult to adhere

LED-T-CL 10 pcs
10 Screws



Curve Clip
Secures on one edge

LED-T-CL1 10 pcs
10 Screws

*Clips to hold indoor InvisiLED tapes sections
Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette*