



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



LMSW102W 24V 5MA 2-BTN SW *Wattstopper*

Catalog Number	LMSW102W
Manufacturer	Wattstopper
Description	<Div>LMSW-100 Series Wall Switches Are Low Voltage Devices For Energy-Saving Manual On/Off Control Of One or More Loads From One or More Locations. They Are Part Of A Digital Lighting Management (DLM) System and Can Control Any Load(S) Connected to DLM Room Controllers.</Div>
Weight per unit	0.2500 (lbs/each)
Product Category	Lighting Controls

Features

indoor/outdoor	Indoor
Input Voltage	24 VDC
Material	ABS
Mounting Type	J-Box
number of buttons	2.0
Number of Switches	2.0
Switch Type	Push

Material, Color, and Finish

Color	White
Finish	Glossy

Descriptions

Description	24V 5MA 2-BTN SW
extra long description	WATT LMSW-102-W Digital Switch, 2-b
Features	<div>LMSW-100 Series Wall Switches are low voltage devices for energy-saving manual on/off control of one or more loads from one or more locations. They are part of a Digital Lighting Management (DLM) system and can control any load(s) connected to DLM room controllers.</div>
Long Description	<div>LMSW-100 Series Wall Switches are low voltage devices for energy-saving manual on/off control of one or more loads from one or more locations. They are part of a Digital Lighting Management (DLM) system and can control any load(s) connected to DLM room controllers.</div>
Product Type	Digital Switch, 2-Button W/Inf



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	Legrand-Wattstopper
GTIN	00754182925452
Manufacturers Part Number	LMSW-102-W
UPC	754182925452

Taxonomies, Classifications, and Categories

Category Description	Residential Switches
Type	SWITCH

Packaging

Carton	1
Weight Per each	0.25

Uses, Certifications, and Standards

Operating Temperature	0°-55°C, 32°-131°F
standard	ROHS, cUL, FCC part 15, UL, RoHS