


# ELLIOTT ELECTRIC SUPPLY 2501 Cavitt Avenue 77801-0000, TX Bryan Phone: 979-779-6630 Fax: 979-779-6620





#### LPCC5 5A 600V TD Class CC Low Peak Fuse

Bussmann Fuses

Catalog Number	LPCC5
Manufacturer	Bussmann Fuses
Description	Low Peak Fuse, Time Delay Fuse Speed, Class CC Fuse, 12 S @ 200% Response Time, 5 A, 600 V Ac;150 V DC, Melamine Tube Material, Dual Element, 0.41 In Diameter, 1.5 IN38.1 MM Overall Length, 0.02 LB
Weight per unit	0.0200 (lbs/each)
Product Category	Current Limiting

#### **Features**

amperage rating	5
connection	Ferrule End X Ferrule End
dimensions	0.4100 IN X 0.4100 IN X 1.5000 IN
element	Dual
media	Yes

#### **Dimensions and Weight**

Size	13/32 In Diameter X 1-1/2 In Length

#### **Descriptions**

Description	5A 600V TD CLASS CC LOW PEAK FUSE
extra long description	BUSS LP-CC-5 LOW PEAK CC TIME DELAY
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Special Features	Rejection Style

#### **Manufacturer Information**

Brand	Eaton Bussmann series
GTIN	00051712180337
UPC	051712180337

### **Taxonomies, Classifications, and Categories**

Category Description	MIDGET FUSES
Туре	FUSE



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2501 Cavitt Avenue 77801-0000, TX Bryan Phone: 979-779-6630 Fax: 979-779-6620

Packaging		
Carton	10	
Weight Per each	0.02	
Uses, Certifications, and Standards		
standard	UL Listed ,CSA Certified,CE Marked,RoHS Compliant	