


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2260 N Burton Ave Suite 100 65803-0000, MO Springfield Phone: 417-429-1665 Fax: 417-429-1666





LPCC7 7A 600V TD Class CC Low Peak Fuse

Bussmann Fuses

Catalog Number	LPCC7
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class CC Fuse, LP-CC, Time-Delay,
	Dual-Element Current Limiting Fuse, 7 A, Rejection Style Fuse,
	Interrupting Rating Of 20 Ka At 150 VDC and 200 Ka At 600 Vac
Weight per unit	0.0200 (lbs/each)
Product Category	Current Limiting

Features

amperage rating	7
connection	Ferrule End X Ferrule End
dimensions	0.4100 IN X 0.4100 IN X 1.5000 IN
element	Dual
Fuse Class	Class CC
interrupt rating	20 kAIC at 150 Vdc200 kAIC at 600 Vac
Material	Melamine Tube
media	Yes
Response Time	12 S at 200%
Voltage Rating	600 Vac, 150 Vdc

Dimensions and Weight



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2260 N Burton Ave Suite 100 65803-0000, MO Springfield Phone: 417-429-1665

Fax: 417-429-1666

D	es	cr	ip	ti	0	ns
		\Box			٠:	4!.

7A 600V TD CLASS CC LOW PEAK FUSE
BUSS LP-CC-7 LOW PEAK CC TIME DELAY
Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Eaton Bussmann Series Class CC fuse, LP-CC, time-delay, dual-element current limiting fuse, 7 A, rejection style fuse, interrupting rating of 20 kA at 150 Vdc and 200 kA at 600 Vac
Low Peak CC Time Delay
Rejection Style

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712180528
Manufacturers Part Number	LP-CC-7
UPC	051712180528

Taxonomies, Classifications, and Categories

Category Description	MIDGET FUSES
Туре	FUSE

Packaging

Carton	10
Weight Per each	0.02

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	UL Listed ,CSA Certified,CE Marked,RoHS Compliant