



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## LPCG757SS 3/4" LT SS Cord Conn (.385-.750)

Arlington Industries

Catalog Number	LPCG757SS
Manufacturer	Arlington Industries
Description	Low-Profile Stainless Steel, Liquid-Tight, and Oil-Tight Strain Relief Cord Connector Furnished With A Sealing Ring and Locknut. Comes With Two Grommets For Wider Cable Selection. Grommet A Supports 0.385" to 0.600" Cord Range, and Grommet B Supports 0.600" to 0.750" Cord Range. Comes In A 3/4" Trade Size.
Weight per unit	0.3400 (lbs/each)
Product Category	Liquid Tight Fittings

### Features

Material	Stainless Steel
media	Yes

### Material, Color, and Finish

Color	Silver
-------	--------

### Dimensions and Weight

Length	1.23
Size	L(1.230) x W(1.230) x H(2.250)
Width	1.23

### Descriptions

Description	3/4" LT SS CORD CONN (.385-.750)
extra long description	ARL LPCG757SS 3/4"STEEL CORD GRP-RN
Long Description	Low-profile stainless steel, liquid-tight, and oil-tight strain relief cord connector furnished with a sealing ring and locknut. Comes with two grommets for wider cable selection. Grommet A supports 0.385" to 0.600" cord range, and Grommet B supports 0.600" to 0.750" cord range. Comes in a 3/4" trade size.
Product Type	3/4"Steel Cord GRP-RNG Stainless Steel
Special Features	Oil Tight, Furnished With Sealing Ring And Locknut

### Manufacturer Information

Brand	Arlington Industries
GTIN	00018997127983
Manufacturers Part Number	LPCG757SS
UPC	018997127983

### Taxonomies, Classifications, and Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Type	Low Profile Strain Relief Cord Connector



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Trade Size

Trade Size ..... 3/4 .....

## Packaging

Carton ..... 10 .....

Package ..... 50 .....

Weight Per each ..... 0.34 .....

## Uses, Certifications, and Standards

standard ..... cULus .....