

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPJ20SPI Buss LPJ-20SPI Low-Peak Class J Ind Bussmann Fuses

Catalog Number	LPJ20SPI
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class J Fuse, LPJ, Time-Delay,
	Dual-Element Current Limiting Fuse, 20 A, Indicating Fuse,
	Interrupting Rating Of 300 Ka At 600 Vac
Weight per unit	0.1100 (lbs/each)
Product Category	Small Dimension Fuses

Features

itaros	
amperage rating	20
connection	Ferrule End X Ferrule End
dimensions	2.2500 IN X 0.8100 IN X 0.8100 IN
element	Dual
Fuse Class	Class J
interrupt rating	100 kAIC Vdc300 kAIC at 600 Vac
media	Yes
Response Time	10 sec at 500%
Voltage Rating	600 Vac, 300 Vdc

Dimensions and Weight

Size	0.81 In Diameter X 2.25 In Length
------	-----------------------------------

Descriptions

Description	BUSS LPJ-20SPI LOW-PEAK CLASS J IND
extra long description	BUSS LPJ-20SPI LOW-PEAK CLASS J IND
Features	Bussmann's UL Class J fuse products extend both our Low-Peak family of products with our LPJ_SP and LPJ_SPI dual-element, time-delay fuses as well as our Limitron line offering fast-acting JKS fuses. The LPJ fuses provide industry leading 300,000 amp interrupting rating at 600Vac RMS Sym and 100kA Vdc while delivering a minimum of 10 seconds of 500 percent rated current ride-through performance which is ideal for sizing of high inrush loads. The LPJ products are available with optional permanent replace fu
Long Description	Eaton Bussmann Series Class J fuse, LPJ, time-delay, dual-element current limiting fuse, 20 A, indicating fuse, interrupting rating of 300 kA at 600 Vac
Product Type	Low-Peak Class J Indicating T/D
Special Features	Non-indicating, High in-rush current motor protection



standard

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information	
Brand	Bussmann Fuses
Manufacturers Part Number	LPJ-20SPI
Taxonomies, Classifications, and Cate	gories
Category Description	GLASS FUSES (and ceramic)
Туре	FUSE
Packaging	
Carton	1
Weight Per each	0.11
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems

CE Marked,RoHS Compliant