

ELLIOTT ELECTRIC SUPPLY8620 E 34th St N 67226-0000, KS Wichita Phone: 316-247-8220 Fow 000 000-0000

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 000-000-0000



LPJ412SP 4-1/2A 600V J TD Fuse

Bussmann Fuses

| Catalog Number | LPJ412SP |
|------------------|--|
| Manufacturer | Bussmann Fuses |
| Description | 4-1/2A 600V Class J Low Peak Dual Element, Time Delay Fuse |
| Weight per unit | 0.1900 (lbs/each) |
| Product Category | Tools & Testers |

Features

| amperage rating | 4.5A |
|------------------|-----------------------------------|
| class | Class J |
| connection | Ferrule End X Ferrule End |
| dimensions | 0.8100 IN X 0.8100 IN X 2.2500 IN |
| element | Dual |
| interrupt rating | 300 kAIC at 600 Vac100 kAIC Vdc |
| Response Time | 10 sec at 500% |
| Voltage Rating | 600 Vac, 300 Vdc |

Dimensions and Weight

| Size | 0.81 In Diameter X 2.25 In Length |
|------|-----------------------------------|
| | |

Descriptions

| Description | 4-1/2A 600V J TD FUSE |
|------------------------|---|
| extra long description | EFSE LPJ-4-1/2SP LOW-PEAK CLASS J T |
| Features | Bussmann's UL Class J fuse products extend both our Low-Peak family of products with our LPJ_SP and LPJ_SPI dual-element, time-delay fuses as well as our Limitron line offering fast-acting JKS fuses. The LPJ fuses provide industry leading 300,000 amp interrupting rating at 600Vac RMS Sym and 100kA Vdc while delivering a minimum of 10 seconds of 500 percent rated current ride-through performance which is ideal for sizing of high inrush loads. The LPJ products are available with optional permanent replace fu |
| Long Description | 4-1/2A 600V Class J Low Peak Dual Element, Time Delay Fuse |
| Product Type | Low-Peak Class J T/D |

Manufacturer Information

| Brand | Eaton |
|---------------------------|----------------|
| GTIN | 00051712522786 |
| Manufacturers Part Number | LPJ412SP |
| UPC | 051712522786 |



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

8620 E 34th St N 67226-0000, KS Wichita Phone: 316-247-8220 Fax: 000-000-0000

| Taxonomies, Classifications, and Cate | gories |
|---------------------------------------|--|
| Category Description | Fuses & Fuse Accessories |
| Туре | FUSE |
| Packaging | |
| Carton | 10 |
| Weight Per each | 0.19 |
| Uses, Certifications, and Standards | |
| Application | Ind Facilities & Factories - Facility: Safety and Security Systems |

CE Marked, RoHS Compliant