

## ELLIOTT ELECTRIC SUPPLY 10131 E 21st St. 74129-0000, OK Tulsa

We Deliver...Lower Cost, Quality Products, & Personal Service

Phone: 918-948-7825 Fax: 918-835-8085



### LR125M 1-1/4" LR FM5 Conduit Body Crouse-Hinds

Catalog Number	LR125M
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 5 Conduit Outlet Body, Malleable Iron, LR Shape, 1-1/4"
Weight per unit	3.8 (lbs/each)
Product Category	Bodies & Covers

#### **Features**

dimensions	8.1200 IN X 2.7500 IN X 2.7500 IN
Form	Form 5

#### Material, Color, and Finish

Finish	Electrogalvanized With Aluminum Acrylic Painted

#### **Dimensions and Weight**

Height	2.75	
Hub Size	1-1/4 in	
Length	8.12	
wiath	2.75	

#### **Descriptions**

Description	1-1/4" LR FM5 CONDUIT BODY
extra long description	CRS-H LR125M 1 1/4 FORM 5 LR COND B
Features	Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h
Long Description	Eaton Crouse-Hinds series Condulet Form 5 conduit outlet body, Malleable iron, LR shape, 1-1/4"
Product Type	1 1/4 Form 5 LR Cond Body Malleable

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274756066
Manufacturers Part Number	LR125M
UPC	782274756066



# ELLIOTT ELECTRIC SUPPLY 10131 E 21st St. 74129-0000, OK Tulsa Phone: 918-948-7825 Fax: 918-835-8085

laxonomies, Classifications, and Cat	egories
Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging	
Carton	5
Weight Per each	3.82
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 514B, CSA C22.2, CUL