

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### LT100G 1" LT Ground Conn

Catalog Number	LT100G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC Straight, Aluminum Ground Lug, Non-Insulated, #4-14 Awg Lug Size, Malleable Iron, 1"
Weight per unit	0.4600 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	2.0600 IN X 0.8100 IN X 0.8100 IN
installation type	THREADED
Material, Color, and Finish	
Color	MALLEABLE IRON
Descriptions	
Description	1" LT GROUND CONN
extra long description	MIDWEST LT100G 1 LT CONN GROUND LUG
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are
	designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, Straight, Aluminum ground lug, Non-insulated, #4-14 AWG lug size, Malleable iron, 1"
Product Type	1 LT Conn Ground Lug
Special Features	With 14 To 4 AWG Aluminum Grounding Lug
Manufacturer Information Brand	EATON CROUSE-HINDS SERIES

#### Mar

Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564260031
Manufacturers Part Number	LT100G
UPC	784564260031

### **Taxonomies, Classifications, and Categories**

Category Description	METALLIC FITTINGS
Туре	Liquidtight connector



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

<b>Trade Size</b> Trade Size	1 in
Packaging	4
Package	5
Weight Per each	0.46
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.2