



## LT20045G 2" 45D LT Ground Conn *Crouse-Hinds*

Catalog Number	LT20045G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Aluminum Ground Lug, Non-Insulated, #4-14 Awg Lug Size, Malleable Iron, 2"
Weight per unit	1.9 (lbs/each)
Product Category	Liquid Tight Fittings

### Features

connection	Threaded
dimensions	4.4400 IN X 3.0000 IN X 4.4400 IN
installation type	THREADED

### Material, Color, and Finish

Color	MALLEABLE IRON
-------	----------------

### Descriptions

Description	2" 45D LT GROUND CONN
extra long description	MIDWEST LT20045G 2 LT 45 DEGREE CON
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Aluminum ground lug, Non-insulated, #4-14 AWG lug size, Malleable iron, 2"
Product Type	2 LT 45 Degree Conn Ground Lug
Special Features	With 14 To 4 AWG Aluminum Grounding Lug

### Manufacturer Information

Brand	Eaton
GTIN	00784564260260
Manufacturers Part Number	LT20045G
UPC	784564260260

### Taxonomies, Classifications, and Categories

Category Description	METALLIC FITTINGS
Type	Liquidtight connector



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5510 West 65th Street  
72209-0000, AR Little Rock  
Phone: 501-565-1785  
Fax: 501-565-0827

## Trade Size

Trade Size 2 in

## Packaging

Carton 1

Weight Per each 1.9

## Uses, Certifications, and Standards

Application Commercial / Institutional Buildings / Structures - Commercial /  
Institutional Buildings / Structures - Other  
standard UL 467, UL 514B, CSA C22.32