



LT25045G 2-1/2" 45D AI LT Conn, #1/0-8AWG GRND Lug *Crouse-Hinds*

Catalog Number	LT25045G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Aluminum Ground Lug, Non-Insulated, #1/0-8 Awg Lug Size, Malleable Iron, 2-1/2"
Weight per unit	5.8 (lbs/each)
Product Category	Liquid Tight Fittings

Features

connection	Threaded
dimensions	8.3100 IN X 4.0000 IN X 8.3100 IN
installation type	THREADED

Material, Color, and Finish

Color	MALLEABLE IRON
-------	----------------

Descriptions

Description	2-1/2" 45D AL LT CONN, #1/0-8AWG GRND LUG
extra long description	MIDWEST LT25045G 2 1/2 LT 45 DEGREE
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Aluminum ground lug, Non-insulated, #1/0-8 AWG lug size, Malleable iron, 2-1/2"
Product Type	2 1/2 LT 45 Degree Conn Ground Lug
Special Features	With 8 To 1/0 AWG Aluminum Grounding Lug

Manufacturer Information

Brand	Eaton
GTIN	00784564260277
Manufacturers Part Number	LT25045G
UPC	784564260277

Taxonomies, Classifications, and Categories

Category Description	METALLIC FITTINGS
Type	Liquidtight connector



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

510 W Jackson Street
38501-0000, TN Cookeville
Phone: 931-271-9933
Fax: 931-545-4298

Trade Size

Trade Size 2 1/2 in

Packaging

Carton 1

Weight Per each 5.82

Uses, Certifications, and Standards

Application Commercial / Institutional Buildings / Structures - Commercial /
Institutional Buildings / Structures - Other

standard UL 467, UL 514B, CSA C22.36