



LTB7545G 3/4" 45D LT Conn

Crouse-Hinds

Catalog Number	LTB7545G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Aluminum Ground Lug, Insulated, #4-14 Awg Lug Size, Malleable Iron, 3/4"
Weight per unit	0.5200 (lbs/each)
Product Category	Liquid Tight Fittings

Features

connection	Threaded
dimensions	2.6900 IN X 1.5600 IN X 2.6880 IN
installation type	THREADED

Material, Color, and Finish

Color	MALLEABLE IRON
-------	----------------

Descriptions

Description	3/4" 45D LT CONN
extra long description	MIDWEST LTB7545G 3/4 LT 45 DEG CONN
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Aluminum ground lug, Insulated, #4-14 AWG lug size, Malleable iron, 3/4"
Product Type	3/4 LT 45 Deg Conn Ground Lug Insulated
Special Features	With 14 To 4 AWG Aluminum Grounding Lug

Manufacturer Information

Brand	Eaton
GTIN	00784564264220
Manufacturers Part Number	LTB7545G
UPC	784564264220

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	Liquidtight connector



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3520 S Sam Houston Pkwy East Suite 900
77047-0000, TX Houston
Phone: 281-412-7049
Fax: 281-412-7314

Trade Size

Trade Size 3/4 in

Packaging

Carton	1
Package	10
Weight Per each	0.52

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.86