

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

MC1222WG250 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' Southwire Company

Manufacturer Description Southwire Company Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90ŰC Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity. Weight per unit Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.53876 Voltage Rating 600V Material, Color, and Finish Conductor Material CU	Southwire Company Catalog Number	MC1222WG250
Description Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90Å*C Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Iddentification. Colors Available Upon Request With Economic Order Quantity. Weight per unit 0,3900 (lbs/each) Product Category Wire Features Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0,53876 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SoIBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90Å*C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	· ·	
Features Conductor Size I2 media Yes Number of Conductors Outside diameter Voltage Rating Outside Material Conductor Material CU Dimensions and Weight Length Description Description Description Description SwC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90°C Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic
Features Conductor Size media Yes Number of Conductors 2 outside diameter 0.53876 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Weight per unit	0.3900 (lbs/each)
Conductor Size 12 media Yes Number of Conductors 2 outside diameter 0.53876 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Product Category	Wire
media Yes Number of Conductors 2 outside diameter 0.53876 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Features	
Number of Conductors outside diameter 0.53876 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Conductor Size	12
outside diameter 0.53876 Voltage Rating 600V Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		
Waterial, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		
Material, Color, and Finish Conductor Material CU Dimensions and Weight Length 250 Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		
Conductor Material Dimensions and Weight Length 250 Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Voltage Rating	600V
Descriptions Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Material, Color, and Finish Conductor Material	CU
Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Dimensions and Weight Length	250
Description 12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250' extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.	Descriptions	
extra long description SWC 55499101 MCNP12/2SolBkRd 2#12N Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		12/2/2 WG MC (BK-RD)(WH-BK)(WH-RD) 250'
Long Description Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90ŰC dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.		SWC 55499101 MCNP12/2SolBkRd 2#12N
Product Type MCNP12/2SOLBKRD 2#12N 12G AA 250C		soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification.
	Product Type	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	Informa	

Brand	Flexible Conduit
GTIN	00032886854774
Manufacturers Part Number	55499101
UPC	032886854774

Taxonomies, Classifications, and Categories

Category Description	BX & MC	
Туре	NPP	

Packaging

99		
Carton	250	
Weight	38.63325	
Weight Per foot	0.39	