



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

475 Boardwalk
78119-2604, TX Kenedy
Phone: 830-299-4593
Fax: 830-583-9886



MC142WG 14/2 WG MC Sol BK/WH/GN Alu Armor *Southwire Company*

Catalog Number	MC142WG
Manufacturer	Southwire Company
Description	Southwire Armorlite Type MC Cable Is Constructed With Soft-Drawn Copper Type THHN/THWN-2 Conductors Rated 90°C Dry and A Bare Copper Grounding Conductor For Sizes 1/0 Awg and Larger. The Conductors Are Cabled Together and A Binder Tape Bearing The Print Legend Is Wrapped Around The Assembly. Aluminum Interlocking Armor Is Applied Over The Assembly. Also Available In Steel. Conductors Are Black With Phase Identification. Colors Available Upon Request With Economic Order Quantity.
Weight per unit	0.0850 (lbs/each)
Product Category	Wire

Features

media	Yes
-------	-----

Descriptions

Description	14/2 WG MC SOL BK/WH/GN ALU ARMOR
extra long description	SWC 68579201 MC14/2SOLTHHN BKWE 14G
Long Description	Southwire Armorlite Type MC Cable is constructed with soft-drawn copper Type THHN/THWN-2 conductors rated 90°C dry and a bare copper grounding conductor for sizes 1/0 AWG and larger. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. Also available in steel. Conductors are black with phase identification. Colors available upon request with economic order quantity.
Product Type	MC14/2SOLTHHN Bkwe 14G AA 250C
Short Description	2" ULTRATITE FLEXIBLE CONDUIT

Manufacturer Information

Brand	Flexible Conduit
GTIN	00032886347122
Manufacturers Part Number	68579201
UPC	032886347122

Taxonomies, Classifications, and Categories

Category Description	BX & MC
----------------------	---------

Availability

Status	Inactive
--------	----------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

475 Boardwalk
78119-2604, TX Kenedy
Phone: 830-299-4593
Fax: 830-583-9886

Packaging

Carton 250

Weight Per each 0.085