



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



MHUB2 3/4" CNDT Hub *Crouse-Hinds*

Catalog Number	MHUB2
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Mhub Conduit Hub, Malleable Iron, 3/4"
Weight per unit	0.2500 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Male Threaded
dimensions	1.8400 IN X 1.6200 IN X 1.5100 IN
Material	Malleable Iron

Material, Color, and Finish

Finish	Zinc Electroplated
--------	--------------------

Dimensions and Weight

Size	3/4 in
------	--------

Descriptions

Description	3/4" CNDT HUB
extra long description	MIDWEST MHUB2 3/4 COND HUB MALLEABL
Features	The use of rigid/IMC conduit remains the preferred choice in many applications because of the physical protection of conductors and long service life of the installation. Consequently, the need to terminate conduit into a box or enclosure creates the need for a hub. The Crouse-Hinds series commercial hub has been developed to provide a lightweight hub that installs quickly and easily, providing a secure termination.
Long Description	Eaton Crouse-Hinds series MHUB conduit hub, Malleable iron, 3/4"
Product Type	3/4 Cond Hub Malleable Iron
Special Features	Weight 25 Lb per 100

Manufacturer Information

Brand	Eaton
GTIN	00784564002860
Manufacturers Part Number	MHUB2
UPC	784564002860

Taxonomies, Classifications, and Categories

Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR
Type	Conduit hub



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	25
Weight Per each	0.25

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
Enclosure standard	NEMA FB-1, Class I Div 2, Class II Div 1 2, Class III Div 1 2 UL 514B, CUL, CSA C22.2