



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

MPNY7509C 3/4" Rubber CBL Tie MNT Base

Abb Installation Products, Inc

| | |
|------------------|---|
| Catalog Number | MPNY7509C |
| Manufacturer | Abb Installation Products, Inc |
| Description | Cable Tie Mounting Base, Natural Nylon 6.6 For Temperatures Up to 70 Degrees Celsius (158 F), Length Of 18.79MM (0.74 Inches), Width Of 18.79MM (0.74 Inches), Height Of 5.08MM (0.20 Inches), Mechanical Strength 40 Newtons (9 Pounds), Hole Size #4, Synthetic Rubber Adhesive Mounting Method, 100 Pack |
| Weight per unit | 0.0019 (lbs/each) |
| Product Category | Miscellaneous |

Features

| | |
|----------|---------------------|
| Material | Nylon/Polyamide 6.6 |
|----------|---------------------|

Material, Color, and Finish

| | |
|-------|---------|
| Color | Natural |
|-------|---------|

Descriptions

| | |
|------------------------|---|
| Description | 3/4" RUBBER CBL TIE MNT BASE |
| extra long description | ABB MPNY-750-9-C CABLE TIE MTG BASE |
| Long Description | Cable Tie Mounting Base, Natural Nylon 6.6 for Temperatures up to 70 Degrees Celsius (158 F), Length of 18.79mm (0.74 Inches), Width of 18.79mm (0.74 Inches), Height of 5.08mm (0.20 Inches), Mechanical Strength 40 Newtons (9 Pounds), Hole Size #4, Synthetic Rubber Adhesive Mounting Method, 100 Pack |
| Product Type | Cable Tie MTG Base Nat .75IN Rubber |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Catamount |
| GTIN | 00728494081526 |
| Manufacturers Part Number | MPNY-750-9-C |
| UPC | 728494081526 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--|
| Category Description | Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps |
| Type | MOUNTING BASE |

Packaging

| | |
|-----------------|---------|
| Carton | 100 |
| Weight Per each | 0.00188 |

Uses, Certifications, and Standards

| | |
|-----------------------|---------------|
| Mounting | Adhesive |
| Operating Temperature | -40 to +185 F |