

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

MSZ101WH Maestro DV 8A 0-10V Occupancy White Lutron

Catalog Number	MSZ101WH	
Manufacturer	Lutron	
Description	Maestro 0-10V Dimmer Occupancy/Vacancy Sensor, Passive Infrared, 8A Fluorescent Ballast or Led Driver, 120-277V, In White	
Weight per unit	0.3000 (lbs/each)	
Product Category	Lighting Occupancy Sensors	
Features		
body	Plastic	
load	8 A/0-10VDC	
media	Yes	
sensing range	900 ft2 (82 m2) major motion coverage/400 ft2 (36 m2) minor motion coverage	
supply voltage	120 to 277	
Material, Color, and Finish Finish	Gloss	
Descriptions		
Description	MAESTRO DV 8A 0-10V OCCUPANCY WHITE	
extra long description	LUT MS-Z101-WH 0-10V DIMMER SENSOR	
Long Description	Maestro 0-10V dimmer occupancy/vacancy sensor, passive infrared, 8A fluorescent ballast or LED driver, 120-277V, in white	
Product Type	Maestro Motion Sensor Switch White	
Special Features	Passive infrared sensors that automatically control the lights in an area. These sensors detect heat from occupants moving within an area to determine when the space is occupied. Combines a Maestro 0-10 V dimmer with an occupancy sensor. Controls 1-10 VDC electronic fluorescent ballast or LED driver load types. Passive infrared motion detection with exclusive Lutron XCT Technology for fine motion detection. 180 degree sensor field-of-view. Up to 30 ft x 30 ft (9 m x 9 m) [900 ft2 (81 m2)] major motion co	
Manufacturer Information Brand	Lutron	
GTIN	00784276099844	
Manufacturers Part Number	MS-Z101-WH	

784276099844



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	Taxonomies,	Classifications,	and Categories	3
--	-------------	------------------	----------------	---

Category Description	Residential dimmers, motion sensors, controls, & photo cells
Туре	Occupancy/Vacancy sensor dimmer,
	multi-location/3-way/single-pole, 0-10 V

Packaging

ckaging	
Carton	1
Weight Per each	0.3

Uses, Certifications, and Standards

Application	Lighting Control
Enclosure	Plastic
environmental conditions	0 to 90% humidity, non-condensing. Indoor use only.
Mounting	WALLBOX
Operating Temperature	32 to 104
standard	UL, cUL, Title 20/24 certified