

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7929 N Sam Houston Pkwy W Suite 100 77064-0000, TX Houston Phone: 281-345-1143

Fax: 281-345-7697



**Packaging** 

Carton

Weight Per each

## NFFLDC40S SLPFTR 128W Led Flood 40K Cooper Lighting Solutions

Catalog Number	NFFLDC40S
Manufacturer	Cooper Lighting Solutions
Description	Led Flood Light, Die-Cast Aluminum, 120 to 277 V Ac;347 V Ac;480 V Ac, 128 W, 70, 16900 LM Brightness (Lumens), 4000 K, Powder Coat, 15-15/16 In Length, 8-11/16 In Width, 12-11/16 In Height, Tempered Glass Lens Material, Slipfitter Mount, +40 °C Operating Temperature, -40 °C Operating Temperature, 60000 H Average Life, 5 Yr Warranty, 20 LB
Weight per unit	19.7 (lbs/each)
Product Category	Led Floodlights
atures	
amperage rating	0.466 (at 277V)
Ballast Type	N/A
battery	N/A
Fixture Type	
Lamp Type	LED
lumens	16,932
media	Yes
Number of Lamps	2
Shape	Rectangular
mensions and Weight	
Size	18.4 IN Length 19.0 IN Width 10.0 IN Height
escriptions	
	SLPFTR 128W LED FLOOD 40K
extra long description	CLS NFFLD-C40-S NFFLD,129W,4000K,UN
Special Features	Die-cast aluminum housing, driver compartment and driver door
anufacturer Information	
Brand	LUMARK
GTIN	00080083801206
UPC	080083801206
xonomies, Classifications, and (	Categories
Category Description	LED FLOODLIGHTS, WALLPACKS, BOLLARDS & LANDSCAPE LIGHTING
Туре	FLOODLIGHT

19.7

7929 N Sam Houston Pkwy W Suite 100 77064-0000, TX Houston Phone: 281-345-1143 Fax: 281-345-7697

## Uses, Certifications, and Standards

Mounting	SLIPFITTER
standard	UL/cUL Listed - Wet Location;RoHS Compliant