



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2900 East Pioneer Parkway Suite 170
76010-0000, TX Arlington
Phone: 817-695-1616
Fax: 817-633-9062



NK6PC7Y NK Copper Patch Cord Cat 6 Off White Utp Cable 7FT

Panduit Corporation

Catalog Number	NK6PC7Y
Manufacturer	Panduit Corporation
Description	The Netkey® Cat 6 Utp Patch Cord Is Constructed Of 24 Awg, Unshielded, Twisted Pair, Stranded, CM Cable With Enhanced Performance Modular Plugs. The Patented Tangle Free Latch Prevents Snags and Provides Easy Release Saving Time On Frequent Moves, Adds, and Changes. The Patch Cord'S Slender Strain Relief Boot Provides Easy Access In High-Density Applications. The Patch Cord Is 7 Feet In Length and Off White.
Weight per unit	0.2900 (lbs/each)
Product Category	Wiring Devices

Features

outside diameter	0.235
Plug Type	Modular Plug
Wire Size	24

Material, Color, and Finish

Color	Off-White
Jacket Material	Polyvinyl Chloride (PVC)

Dimensions and Weight

Length	7.00
--------	------

Descriptions

Description	NK COPPER PATCH CORD CAT 6 OFF WHITE UTP CABLE 7FT
extra long description	PAN NK6PC7Y NetKey® Cat 6 24 AWG UT
Long Description	The NetKey® Cat 6 UTP Patch Cord is constructed of 24 AWG, unshielded, twisted pair, stranded, CM cable with enhanced performance modular plugs. The patented tangle free latch prevents snags and provides easy release saving time on frequent moves, adds, and changes. The patch cord's slender strain relief boot provides easy access in high-density applications. The patch cord is 7 feet in length and off white.
Product Type	Netkey® Cat 6 24 Awg Utp Patch Cord, 7 FT, lw

Manufacturer Information

Brand	PANDUIT
GTIN	00074983055692
Manufacturers Part Number	NK6PC7Y
UPC	074983055692



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2900 East Pioneer Parkway Suite 170
76010-0000, TX Arlington
Phone: 817-695-1616
Fax: 817-633-9062

Taxonomies, Classifications, and Categories

Category Description	Datcom Wiring Devices and Accessories
Type	Patch Cord

Packaging

Carton	1
Package	10
Weight Per each	0.29

Uses, Certifications, and Standards

Application	155 Mb/s ATM, 622 Mb/s ATM, 1.2 Gb/s ATM;Token;Used in all work area outlets and patch panels;wired to be compatible with both T568A and T568B wiring schemes. Suitable for Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), and 1000BASE-T (Gigabit Ethernet)
standard	Complies with ANSI/TIA-1096-A;Exceeds ANSI/TIA-568.2-D Category 6 and ISO 11801 Class E channel requirements at swept frequencies up to 250 MHz;Mee;Meets ANSI/TIA-568.2-D and ISO 11801 Category 6 component requirements at swept frequencies up to 250 MHz