



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## NNC37X37WH2 37MX37MMX2M WH Wire DCT Panduit Corporation

Catalog Number	NNC37X37WH2
Manufacturer	Panduit Corporation
Description	The NNC37X37WH2 Halogen-Free Wide Slot Wiring Duct Is Used to Route, Protect, and Manage Wires Near Sensitive Electronic Equipment and In Environments Where Heat Resistance or Public Safety Is A Concern. UL 94 Flame Class Of V-0 With A UL Recognized Continuous-Use Temperature Up to 95°C (203°F). Halogen-Free, Polyphenylene Oxide (Ppo). Mounting Holes Provided. 1.41" X 1.46" (35.8 MM X 37.1 MM) and 6.6' (2 M) Long. Cover Included. Color White. 5 Pieces Per Package.
Weight per unit	1.5 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

### Features

connection	DIN Standard Mounting Holes
media	Yes

### Material, Color, and Finish

Color	White
-------	-------

### Dimensions and Weight

Length	NA
Size	1.46 x 1.41
Width	1.46

### Descriptions

Description	37MX37MMX2M WH WIRE DCT
extra long description	PAN NNC37X37WH2 Panduct® NNC37X37WH
Long Description	The NNC37X37WH2 Halogen-Free Wide Slot Wiring Duct is used to route, protect, and manage wires near sensitive electronic equipment and in environments where heat resistance or public safety is a concern. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 95°C (203°F). Halogen-Free, Polyphenylene Oxide (PPO). Mounting holes provided. 1.41" x 1.46" (35.8 mm x 37.1 mm) and 6.6' (2 m) long. Cover included. Color White. 5 pieces per package.
Product Type	Panduct® NNC37X37WH2 Wide Slot Duct, White, Hal-Free Ppo, 1.



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

Brand	PANDUIT
GTIN	00074983442775
Manufacturers Part Number	NNC37X37WH2
UPC	074983442775

## Taxonomies, Classifications, and Categories

Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Type	Wiring Duct Base with Cover

## Packaging

Carton	1
Package	20
Weight Per meter	1.47

## Uses, Certifications, and Standards

Application	NNC Wiring Duct is Used to Route, Protect, and Manage Wires near Sensitive Electronic Equipment and in Environments where Heat Resistance or Public Safety is a Concern
standard	RoHS Compliant, UL Recognized, CE Compliant, DIN 43659 Compliant, EN45545-2 HL1 & HL3 Compliant, BABA Compliant