

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

760 Ford St. 80915-0000, CO Colorado Springs Phone: 719-559-2456 Fax: 719-867-4287



Carton Package

Weight Per each

NTC50 1/2" Rigid Threadless Raintight Connector Appleton/Oz Gedney

Catalog Number	NTC50
Manufacturer	Appleton/Oz Gedney
Description	Compression Connector, Size: 1/2 In, Connection: Male Threaded X Compression, Material: Steel, Length: 1.26 In, Thread Length: 0.38 In, Diameter: 1.31 In, Standard: UI 514B, UI File Number E14814, Nema FB-1, For Use to Secure and Terminate Steel Emt to Knockouts and Concrete Tight Box
Weight per unit	0.1500 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel
Features	
connection	Male Threaded X Compression
Material	Steel
Dimensions and Weight	
Size	1/2
Descriptions	
Description	1/2" RIGID THREADLESS RAINTIGHT CONNECTOR
extra long description	APP NTC-50 1/2 IN CONN NO THRD RGD
Long Description	Compression Connector, Size: 1/2 IN, Connection: Male Threaded X Compression, Material: Steel, Length: 1.26 IN, Thread Length: 0.38 IN, Diameter: 1.31 IN, Standard: UL 514B, UL File Number E14814, NEMA FB-1, For Use To Secure And Terminate Steel EMT To Knockouts And Concrete Tight Box
Product Type	1/2 In Conn No THRD RGD Cond
Special Features	Concretetight
Vlanufacturer Information	
Brand	Appleton
GTIN	00781381637701
Manufacturers Part Number	NTC-50
UPC	781381637701
Taxonomies, Classifications, and (Categories
Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR
Туре	Compression Connector
Packaging	
0 - 1	50

50

200

0.15



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

760 Ford St. 80915-0000, CO Colorado Springs Phone: 719-559-2456 Fax: 719-867-4287

Uses, Certifications, and Standards

Application	For Use To Secure And Terminate Steel EMT To Knockouts And
	Concrete Tight Box
standard	UL 514B, UL File Number E14814, NEMA FB-1