

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



P261209 60W Fan Light Kit *Progress Lighting*

Catalog Number	P261209
Manufacturer	Progress Lighting
Description	Brushed Nickel Three-Light Fan Kit With Alabaster Style Glass Bowl. Elegant Alabaster Glass Conceals Light Bulbs and Casts An Inviting Illumination In Any Size Room. Corresponding Pull Chain Features Chrome Finish With A Maple Oak Fob. Universal Style Lets You Use With Any Indoor Fan That Accept An Accessory Light. Quick-Connect Wiring Makes The Installation Process Quick and Easy.
Weight per unit	3.7 (lbs/each)
Product Category	Lighting
Features	
Lamp Included	Yes
Lamp Type	B-12
Material	Steel
Number of Lamps	3
Socket Type	sockets
Voltage Rating	120
Wattage	40
Material, Color, and Finish	
Color	Nickel
Finish	PLATED
Style	Transitional
Dimensions and Weight	
Height	6
Length	10.75
Width	10.75
Descriptions	
Description	60W FAN LIGHT KIT

Des

Description	60W FAN LIGHT KIT
extra long description	PROG P2612-09 AirPro 3-40W CAND FAN
Long Description	Brushed Nickel three-light fan kit with alabaster style glass bowl. Elegant alabaster glass conceals light bulbs and casts an inviting illumination in any size room. Corresponding pull chain features Chrome finish with a maple oak fob. Universal style lets you use with any indoor fan that accept an accessory light. Quick-connect wiring makes the installation process quick and easy.
Product Type	Airpro 3-40W Cand Fan LT Kit Gray



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

nation

Brand	PROGRESS	
GTIN	00785247114405	
Manufacturers Part Number	P2612-09	
UPC	785247114405	

Taxonomies, Classifications, and Categories

Category Description	DECORATIVE RESIDENTIAL
Type	Bowl

Packaging

okugirig	
Carton	1
Weight Per each	3.7

Uses, Certifications, and Standards

standard UL-CUL	
-----------------	--