

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Size

PD5NEWH Caseta 500W Elv Mult W/Neutral White

Oalala Nasalaa	DDENEMAL
Catalog Number	PD5NEWH
Manufacturer	Lutron
Description	Lutron Caseta Wireless Elv+ Smart Dimmer Switch, With Phase Selectable Dimming For Led (250W), MLV (400W), Elv (500W), and Incandescent/Halogen (500W) Lighting, 120V, White
Weight per unit	0.2500 (lbs/each)
Product Category	Lighting Dimmers
Features	
Connection Type	Wire Leads
insulation	Plastic
media	Yes
Poles	1
Switch Type	Push button
Voltage Rating	120
Wattage	500
Material, Color, and Finish	
Color	White
Finish	Gloss
Dimensions and Weight	

4.69 x 2.94;119 x 75



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_				•
11	2	API	nt	IARC
	_			ions
$\boldsymbol{-}$	VJ	v ı .	\sim \sim	

PD-5NE-WH Cas ta ELV Dimmer 250 c Caseta ELV+ Smart Dimmer Switch with phase selectable nming works with up to 250W of dimmable LED, 500W of andescent/halogen/electronic low-voltage (ELV), or 400-Watt magnetic low-voltage (MLV); Neutral wire connection and Watt minimum load required for all load types. Out of the k, the dimmer is set to reverse phase for //incandescent/halogen light loads. However, since it is phase ective, the dimmer output can be changed to forward phase
nming works with up to 250W of dimmable LED, 500W of andescent/halogen/electronic low-voltage (ELV), or 400-Watt magnetic low-voltage (MLV); Neutral wire connection and Watt minimum load required for all load types. Out of the x, the dimmer is set to reverse phase for //incandescent/halogen light loads. However, since it is phase
MLV lighting loads and other certain LED
ron Caseta Wireless ELV+ Smart Dimmer Switch, with Phase ectable Dimming for LED (250W), MLV (400W), ELV (500W), d Incandescent/Halogen (500W) lighting, 120V, White
s Ta Elv Dimmer 250W Led White
ntrols 250 W LED (screw-base), 500 W incandescent/halogen, 0 VA (300 W) magnetic low-voltage, 500 W electronic v-voltage, 400 W Hi-lume 1 percent 2-wire LED driver, or 3.3 A Wire fluorescent ballast loads. Simple, intuitive design with off and raise/lower buttons. Provides true dimming from

Manufacturer Information

Brand	Lutron
GTIN	00784276217699
Manufacturers Part Number	PD-5NE-WH
UPC	784276217699

Taxonomies, Classifications, and Categories

Category Description	Residential dimmers, motion sensors, controls, & photo cells
Туре	Wireless in-wall dimmer, multi-location/single-pole

Packaging

Carton	1	
Weight Per each	0.25	

Uses, Certifications, and Standards

Application	Lighting Control
Enclosure	Plastic
environmental conditions	0 to 90% humidity, non-condensing. Indoor use only.
Mounting	WALLBOX
standard	UL, CUL, FCC, NOM, ICC, IFTEL