

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

903 Mississippi Ave 76301-0000, TX Wichita Falls Phone: 940-257-6832 Fax: 940-257-6833



PLG125 1-1/4" Recessed Plug Appleton/Oz Gedney

Catalog Number	PLG125
Manufacturer	Appleton/Oz Gedney
Description	Unilets Recessed Head Close-Up Plug, Size: 1-1/4 In, Material: Malleable Iron, Finish: Zinc Electroplate, Connection: Tapered MNPT, Standard: UI 886 (1203), UI File Number E10444, Csa C22.2 No. 25 and 30, Csa 065181, UI Listed For Class I
Weight per unit	0.3300 (lbs/each)
Product Category	Bar Hangers & Outlet Box Accy.
eatures	
connection	Tapered MNPT
Material	Malleable Iron
Naterial, Color, and Finish	
Finish	Electro Zinc Plated
Dimensions and Weight	
Size	1-1/4
Descriptions	
Description	1-1/4" RECESSED PLUG
extra long description	APP PLG-125 PLUG 1-1/4 REC HEAD CLO
Long Description	UNILETS Recessed Head Close-Up Plug, Size: 1-1/4 IN, Material Malleable Iron, Finish: Zinc Electroplate, Connection: Tapered MNPT, Standard: UL 886 (1203), UL File Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I
Product Type	Plug 1-1/4 Rec Head Close-Up
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity; Explosion proof, dust-ignition proof; Smooth, rounded integral bushing in each hub protects conductor insulation
/lanufacturer Information	
Brand	Appleton
GTIN	00781381652155
Manufacturers Part Number	PLG-125
UPC	781381652155

Taxonomies, Classifications, and Categories

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs,
	Knockout Plugs
Туре	Recessed Head Close-Up Plug



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

903 Mississippi Ave 76301-0000, TX Wichita Falls Phone: 940-257-6832 Fax: 940-257-6833

Packaging	
Carton	25
Package	100
Weight Per each	0.33
Uses, Certifications, and Star	ndards
Application	For Use With Threaded Rigid Metal Conduit and IMC
standard	And Class III; Class II, Groups E, F, G; UL 886 (1203), UL File
	Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed

For Class I, Groups B, C, D