



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1105 West Sanger
88240-0000, NM Hobbs
Phone: 575-397-2122
Fax: 575-397-2178



PLG50RA 1/2" Alu Insert Plug *Appleton/Oz Gedney*

Catalog Number	PLG50RA
Manufacturer	Appleton/Oz Gedney
Description	Unilets Recessed Head Close-Up Plug, Size: 1/2 In, Material: Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered MNPT, Standard: UI 886 (1203), UI File Number E10444, Csa C22.2 No. 25 and 30, Csa 065181, UI Listed For Class I, Groups
Weight per unit	0.0200 (lbs/each)
Product Category	Bar Hangers & Outlet Box Accy.

Features

connection	Tapered MNPT
Material	Aluminum

Material, Color, and Finish

Finish	Epoxy Powder Coat
--------	-------------------

Dimensions and Weight

Size	1/2
------	-----

Descriptions

Description	1/2" ALU INSERT PLUG
extra long description	APP PLG50RA PLUG 1/2 REC HEAD CLOSE
Long Description	UNILETS Recessed Head Close-Up Plug, Size: 1/2 IN, Material: Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered MNPT, Standard: UL 886 (1203), UL File Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I, Groups
Product Type	Plug 1/2 Rec Head Close-Up-Alu
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity;Explosionproof, dust-ignitionproof;Smooth, rounded integral bushing in each hub protects conductor insulation

Manufacturer Information

Brand	Appleton
GTIN	00781381455565
Manufacturers Part Number	PLG50RA
UPC	781381455565

Taxonomies, Classifications, and Categories

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs
Type	Recessed Head Close-Up Plug



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1105 West Sanger
88240-0000, NM Hobbs
Phone: 575-397-2122
Fax: 575-397-2178

Packaging

Carton	50
Package	500
Weight Per each	0.02

Uses, Certifications, and Standards

Application	For Use With Threaded Rigid Metal Conduit and IMC
standard	And Class III;Class II, Groups E, F, G;UL 886 (1203), UL File Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I, Groups A, B, C, D