



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1811 N. University Suite 100
70507-0000, LA Lafayette
Phone: 337-235-7681
Fax: 337-235-7725

PLT1MC Cable Tie, 3.9L (99MM), Miniature, Nylon, Natural *Panduit Corporation*

Catalog Number	PLT1MC
Manufacturer	Panduit Corporation
Description	Panduit PLT1M-C Locking Cable Ties Are Designed to Satisfy The Needs Of General Applications, While Delivering Consistent Performance and Reliability. Featuring A Curved Tip to Allow For Easy Pick Up From Flat Surfaces and Faster Initial Threading. Miniature Cross Section, 3.9" (99MM) Length. Made Of Nylon 6.6, Are Natural In Color and Come In Packages Of 100.
Weight per unit	0.1500 (lbs/each)
Product Category	Cable Ties & Wraps

Features

media	Yes
Tensile Strength	18

Dimensions and Weight

Length	3.94
Thickness	0.05

Descriptions

Description	CABLE TIE, 3.9L (99MM), MINIATURE, NYLON, NATURAL
extra long description	PAN PLT1M-C Pan-Ty® PLT1M-C Cable T
Long Description	Panduit PLT1M-C Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Miniature cross section, 3.9" (99mm) length. Made of Nylon 6.6, are natural in color and come in packages of 100.
Product Type	Pan-Ty® PLT1M-C Cable Tie, PA6.6, 3.9"L, 18LB, PK100
Special Features	Indoor

Manufacturer Information

Brand	Panduit®
GTIN	00074983540044
Manufacturers Part Number	PLT1M-C
UPC	074983540044

Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Type	Premium Cable Tie



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1811 N. University Suite 100
70507-0000, LA Lafayette
Phone: 337-235-7681
Fax: 337-235-7725

Packaging

Carton	100
Package	1000
Weight Per each	0.15

Uses, Certifications, and Standards

standard	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant
----------	---