



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



PRNIPAL34X5 3/4X5 Redhot Alu Nipple

Robroy/Plasti-Bond

Catalog Number	PRNIPAL34X5
Manufacturer	Robroy/Plasti-Bond
Description	Nipple, 40 Mil Gray PVC Coated (Outside), 2 Mil Red Urethane Coated (Inside, Thread) Aluminum Material; 5 Inch; Rigid Conduit Used On; UL Approval; 1.13 Inch Diameter; 3/4 Inch Trade Size; REDH2OT. Brand; Installation Threaded Male; Prnip Model
Weight per unit	0.1500 (lbs/each)
Product Category	Aluminum

Features

Material	40 MIL GRAY PVC COATED (OUTSIDE), 2 MIL RED URETHANE COATED (INSIDE, THREAD) ALUMINUM
----------	---

Dimensions and Weight

Diameter	1.13 INCH
Length	5 INCH

Descriptions

Commodity Description	ELBOWS-COUPPLINGS-NIPPLES - ALUMINUM
Description	3/4X5 REDHOT ALU NIPPLE
extra long description	ALUMINUM MATERIAL; 2 MIL RED URETHANE (INTERIOR)/40 MIL GRAY PVC (EXTERIOR)/CLEAR URETHANE COATED (THREAD) FINISH; 5 INCH; UL (CANADA AND US), UL 6A, CSA C22.2 APPROVAL; ISO 9001 APPLICABLE STANDARD; 25 PER PACK STANDARD PACKAGE; 3/4 INCH TRADE SIZE; THREADED END TYPE; DIAMETER 1.3/8 INCH; THREAD PROTECTOR COLOR RED; PRNIP-AL MODEL
Long Description	NIPPLE, 40 MIL GRAY PVC COATED (OUTSIDE), 2 MIL RED URETHANE COATED (INSIDE, THREAD) ALUMINUM MATERIAL; 5 INCH; RIGID CONDUIT USED ON; UL APPROVAL; 1.13 INCH DIAMETER; 3/4 INCH TRADE SIZE; REDH2OT. BRAND; INSTALLATION THREADED MALE; PRNIP MODEL
Product Type	Nipple

Manufacturer Information

Brand	PLASTIBOND
GTIN	00784011220779
Manufacturers Part Number	PRNIP-AL-3/4X5
Model	PRNIP
UPC	784011220779

Taxonomies, Classifications, and Categories

Category Description	ALL PLASTIBOND FITTINGS
----------------------	-------------------------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Trade Size

Trade Size 3/4 INCH

Availability

Manufacturer Status Non-Stock

Packaging

Carton 1

Package 25

Weight Per each 0.15

Uses, Certifications, and Standards

Approval UL

Installation THREADED MALE

Used On RIGID CONDUIT