


ELLIOTT ELECTRIC SUPPLY 201 South Persimmon Street 77375-6855, TX Tomball Phone: 281-357-5300 South Persimmon Street 77375-6855, TX Tomball Phone: 281-357-5300 South Persimmon Street 77375-6855, TX Tomball Phone: 281-357-5005

We Deliver...Lower Cost, Quality Products, & Personal Service





PS20AC1WL 20A 120/277VAC B+S Wire SP Lock SW WH

Pass & Seymour/Legrand

Catalog Number	PS20AC1WL
Manufacturer	Pass & Seymour/Legrand
Description	1-Pole Lock Switch, Back and Side-Wire, 20A 120/277V
Weight per unit	0.2142 (lbs/each)
Product Category	Gen Purpose Switches

Features

action	SP
actuator	Toggle
amperage rating	20
Contact Rating	20 Amp, 120/277 VAC
indoor/outdoor	Indoor
insulation	False
Load Rating	20 A @ 120/277 VAC
Load Type	Universal, CFL, Halogen, Xenon, LED, Fluorescent, Incandescent
Material	Thermoplastic
Mounting Type	Wall Box
Number of Gangs	1
Number of Switches	1.0
Poles	1
Switch Type	Toggle
throw type	Single Throw
Voltage	120/277 V
Voltage Rating	120/277
Wall Plate Included	NO
Wire Size	#14 - #10 Awg

Material, Color, and Finish

Finish	Matte

Dimensions and Weight

Size	3.3	11
∖17 ∆	₹ ₹	
JIZU	J.J	

Descriptions

Description	20A 120/277VAC B+S WIRE SP LOCK SW WH
extra long description	P&S PS20AC1WL 20A 120/277VAC B+S WI
Features	Chemical Resistant
Long Description	1-Pole Lock Switch, Back and Side-Wire, 20A 120/277V
Product Type	20A 120/277VAC B+S Wire SP Lock SW W
Special Features	Heavy duty switch, back & side wire, shallow design for ease of installation with Key lock



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

201 South Persimmon Street 77375-6855, TX Tomball Phone: 281-357-5300

Fax: 281-357-5005

V	lanuí	acturer l	Information
---	-------	-----------	-------------

Brand	Pass and Seymour	
GTIN	00785007196450	
Manufacturers Part Number	PS20AC1-WL	
UPC	785007196450	

Taxonomies, Classifications, and Categories

Category Description	Residential plates
Туре	SWITCH

Trade Size

Λ	20.0
Amperage	20.0

Packaging

J		
Carton	1	
Package	50	
Weight Per each	0.2142	

Uses, Certifications, and Standards

Application	Commercial/Residential
Mounting	WALL
standard	CULUS, UL20, FEDSPEC