



CAM PROD MALE PROT CAP

Features & Benefits

Quality Materials, durability, and time-tested design

Specifications

General Info

|              |                       |                    |                         |
|--------------|-----------------------|--------------------|-------------------------|
| Product Line | Pass & Seymour        | Color              | Green                   |
| UPC Number   | 785007308440          | Country Of Origin  | Mexico                  |
| Material     | Nylon                 | Application Sector | Commercial, Industrial  |
| Standard     | UL Listed, CSA Listed | Warranty Type      | 1-Year Limited Warranty |
| Type         | Protection Adapter    |                    |                         |

Technical Information

|                          |                                                                 |
|--------------------------|-----------------------------------------------------------------|
| Environmental Conditions | UL94 V2, Maximum Continuous +75°C, minimum -40°C without impact |
|--------------------------|-----------------------------------------------------------------|



CAM PROD MALE PROT CAP

Features & Benefits

Quality Materials, durability, and time-tested design

Specifications

General Info

|              |                       |                    |                         |
|--------------|-----------------------|--------------------|-------------------------|
| Product Line | Pass & Seymour        | Color              | Green                   |
| UPC Number   | 785007308440          | Country Of Origin  | Mexico                  |
| Material     | Nylon                 | Application Sector | Commercial, Industrial  |
| Standard     | UL Listed, CSA Listed | Warranty Type      | 1-Year Limited Warranty |
| Type         | Protection Adapter    |                    |                         |

Technical Information

|                          |                                                                 |
|--------------------------|-----------------------------------------------------------------|
| Environmental Conditions | UL94 V2, Maximum Continuous +75°C, minimum -40°C without impact |
|--------------------------|-----------------------------------------------------------------|