



Pass and Seymour  
**20A, 125V Extra-Hard Use Spec-Grade Connector, Black and White**  
Part No. PS5369X

Straight Blade Connector 2-Pole 3-Wire 20A 125A



## Features & Benefits

Unit arrives completely ready-to-wire, cuts installation time significantly.

Nylon housing provides impact and chemical resistance. Rugged two-piece cord grip provides more uniform cord retention. Internal dust shield keeps terminals free of contaminants.

Tri-drive assembly screws are standard on all Specification Grade plugs and connectors.

All 3-wire terminals located on the same plane, allows for quick wire termination from any angle.

Heavy-duty brass alloy blades and contacts, resist heat rise, provide excellent conductivity.

Cord-grip screws recessed to protect installer against screwdriver head slippage.

For covering patents, see  
[www.legrand.us/patents](http://www.legrand.us/patents).

## Specifications

### General Info

|              |                     |                    |            |
|--------------|---------------------|--------------------|------------|
| Product Line | Pass & Seymour      | Color              | Black      |
| UPC Number   | 785007237030        | Country Of Origin  | Mexico     |
| Features     | Corrosion Resistant | Application Sector | Industrial |
| Standard     | UL 498, FEDSPEC     | Warranty Type      | 1-Year     |
| Type         | Connector           |                    |            |

### Dimensions

|                  |          |                   |          |
|------------------|----------|-------------------|----------|
| Product Width US | 1.516 in | Product Length US | 2.638 in |
|------------------|----------|-------------------|----------|

### Listing Agencies / 3rd Party Agencies

|              |     |
|--------------|-----|
| cULus Listed | Yes |
|--------------|-----|

### Additional Information

|                               |     |
|-------------------------------|-----|
| Product Environmental Profile | Yes |
|-------------------------------|-----|

Technical Information

|                         |                |                |                |
|-------------------------|----------------|----------------|----------------|
| Connector Style         | Straight Blade | Flanged        | No             |
| Terminal Accommodation  | #4 AWG         | Connection     | Wire Grounding |
| Number of Wires         | 3              | Amperage       | 20 A           |
| Number of Poles         | Double Pole    | Indoor/Outdoor | Indoor         |
| NEMA Configuration Code | 5-20R          | Voltage        | 125.0 V        |



Pass and Seymour  
**20A, 125V Extra-Hard Use Spec-Grade Connector, Black and White**  
Part No. PS5369X

Straight Blade Connector 2-Pole 3-Wire 20A 125A



## Features & Benefits

Unit arrives completely ready-to-wire, cuts installation time significantly.

Nylon housing provides impact and chemical resistance. Rugged two-piece cord grip provides more uniform cord retention. Internal dust shield keeps terminals free of contaminants.

Tri-drive assembly screws are standard on all Specification Grade plugs and connectors.

All 3-wire terminals located on the same plane, allows for quick wire termination from any angle.

Heavy-duty brass alloy blades and contacts, resist heat rise, provide excellent conductivity.

Cord-grip screws recessed to protect installer against screwdriver head slippage.

For covering patents, see  
[www.legrand.us/patents](http://www.legrand.us/patents).

## Specifications

### General Info

|              |                     |                    |            |
|--------------|---------------------|--------------------|------------|
| Product Line | Pass & Seymour      | Color              | Black      |
| UPC Number   | 785007237030        | Country Of Origin  | Mexico     |
| Features     | Corrosion Resistant | Application Sector | Industrial |
| Standard     | UL 498, FEDSPEC     | Warranty Type      | 1-Year     |
| Type         | Connector           |                    |            |

### Dimensions

|                  |          |                   |          |
|------------------|----------|-------------------|----------|
| Product Width US | 1.516 in | Product Length US | 2.638 in |
|------------------|----------|-------------------|----------|

### Listing Agencies / 3rd Party Agencies

|              |     |
|--------------|-----|
| cULus Listed | Yes |
|--------------|-----|

### Additional Information

|                               |     |
|-------------------------------|-----|
| Product Environmental Profile | Yes |
|-------------------------------|-----|

Technical Information

|                         |                |                |                |
|-------------------------|----------------|----------------|----------------|
| Connector Style         | Straight Blade | Flanged        | No             |
| Terminal Accommodation  | #4 AWG         | Connection     | Wire Grounding |
| Number of Wires         | 3              | Amperage       | 20 A           |
| Number of Poles         | Double Pole    | Indoor/Outdoor | Indoor         |
| NEMA Configuration Code | 5-20R          | Voltage        | 125.0 V        |