



Turnlok Registered Plug 3-Wire 15A 125A

## Features & Benefits

|                                                                                             |                                                                                                                                                      |
|---------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Quick-thread assembly screws and cord-grip screws come backed-out, ready-to-wire.           | Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.                                |
| Raised ribs provide non-slip gripping profile for turning to lock and unlock.               | Double dovetail design provides superior protection against cord pull-out forces.                                                                    |
| Impact- and corrosion-resistant durable nylon 6/6 shell material.                           | Rounded back contour reduces snags and hang-ups on the job site.                                                                                     |
| Scallop shell design provides non-slip gripping surface for insertion and withdrawal.       | Visible stamped NEMA configuration and device rating.                                                                                                |
| New-design external cord grips provide visible assurance of safe and proper cord retention. | Integral flexible rubber cord grommet conforms to and seals around SO cord to provide protection from oils, water, or chips entering wiring chamber. |

## Specifications

### General Info

|              |                |                    |            |
|--------------|----------------|--------------------|------------|
| Product Line | Pass & Seymour | Color              | Black      |
| UPC Number   | 785007236545   | Country Of Origin  | Mexico     |
| Features     | Locking        | Application Sector | Industrial |
| Standard     | UL 498         | Warranty Type      | 1-Year     |
| Type         | Plug           |                    |            |

### Dimensions

|                  |          |                   |          |
|------------------|----------|-------------------|----------|
| Product Width US | 1.516 in | Product Length US | 1.752 in |
|------------------|----------|-------------------|----------|

---

Additional Information

---

|                               |     |
|-------------------------------|-----|
| Product Environmental Profile | Yes |
|-------------------------------|-----|

---

Technical Information

---

|                 |         |         |    |
|-----------------|---------|---------|----|
| Connector Style | Locking | Flanged | No |
|-----------------|---------|---------|----|

---

|                        |        |                 |   |
|------------------------|--------|-----------------|---|
| Terminal Accommodation | #4 AWG | Number of Wires | 3 |
|------------------------|--------|-----------------|---|

---

|          |      |                 |             |
|----------|------|-----------------|-------------|
| Amperage | 15 A | Number of Poles | Double Pole |
|----------|------|-----------------|-------------|

---

|                |        |                         |        |
|----------------|--------|-------------------------|--------|
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L5-15P |
|----------------|--------|-------------------------|--------|

---

|         |         |  |  |
|---------|---------|--|--|
| Voltage | 125.0 V |  |  |
|---------|---------|--|--|

---



Turnlok Registered Plug 3-Wire 15A 125A

## Features & Benefits

|                                                                                             |                                                                                                                                                      |
|---------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Quick-thread assembly screws and cord-grip screws come backed-out, ready-to-wire.           | Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.                                |
| Raised ribs provide non-slip gripping profile for turning to lock and unlock.               | Double dovetail design provides superior protection against cord pull-out forces.                                                                    |
| Impact- and corrosion-resistant durable nylon 6/6 shell material.                           | Rounded back contour reduces snags and hang-ups on the job site.                                                                                     |
| Scallop shell design provides non-slip gripping surface for insertion and withdrawal.       | Visible stamped NEMA configuration and device rating.                                                                                                |
| New-design external cord grips provide visible assurance of safe and proper cord retention. | Integral flexible rubber cord grommet conforms to and seals around SO cord to provide protection from oils, water, or chips entering wiring chamber. |

## Specifications

### General Info

|              |                |                    |            |
|--------------|----------------|--------------------|------------|
| Product Line | Pass & Seymour | Color              | Black      |
| UPC Number   | 785007236545   | Country Of Origin  | Mexico     |
| Features     | Locking        | Application Sector | Industrial |
| Standard     | UL 498         | Warranty Type      | 1-Year     |
| Type         | Plug           |                    |            |

### Dimensions

|                  |          |                   |          |
|------------------|----------|-------------------|----------|
| Product Width US | 1.516 in | Product Length US | 1.752 in |
|------------------|----------|-------------------|----------|

---

Additional Information

---

|                               |     |
|-------------------------------|-----|
| Product Environmental Profile | Yes |
|-------------------------------|-----|

---

Technical Information

---

|                 |         |         |    |
|-----------------|---------|---------|----|
| Connector Style | Locking | Flanged | No |
|-----------------|---------|---------|----|

---

|                        |        |                 |   |
|------------------------|--------|-----------------|---|
| Terminal Accommodation | #4 AWG | Number of Wires | 3 |
|------------------------|--------|-----------------|---|

---

|          |      |                 |             |
|----------|------|-----------------|-------------|
| Amperage | 15 A | Number of Poles | Double Pole |
|----------|------|-----------------|-------------|

---

|                |        |                         |        |
|----------------|--------|-------------------------|--------|
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L5-15P |
|----------------|--------|-------------------------|--------|

---

|         |         |  |  |
|---------|---------|--|--|
| Voltage | 125.0 V |  |  |
|---------|---------|--|--|

---