

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

PTRA6SOL 90 Degree 6" PT CNTR Solid

Pass & Seymour/Legrand

Catalog Number	PTRA6S0L
Manufacturer	Pass & Seymour/Legrand
Description	Plugtail Registered Connectors, Right Angle, Solid, 6-Inch Plugtail
	Registered Devices and Connectors Mean That Device Installation
	Is The Same Regardless Of Skill Level Of The Installer. The
	UI-Listed Connectors Are Keyed to Ensure Proper Wiring
	Installation Into Each Receptacle.
Weight per unit	0.0682 (lbs/each)
Product Category	Outlets, Jacks, & Plates

Features

Dielectric Strength	Withstands 2000V minimum
media	Yes
Number of Wires	3
Poles	2
Wattage	Electrical power is expressed in Amps and Volts.
Wire Size	12 AWG

Material, Color, and Finish

Color	White
Finish	Matte

Dimensions and Weight

Size	7.5	

Descriptions

Description	90 DEGREE 6" PT CNTR SOLID
extra long description	P&S PTRA6SOL 90 DEGREE 6 IN PT CNTR
Long Description	PlugTail Registered Connectors, Right Angle, Solid, 6-inch PlugTail Registered devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure proper wiring installation into each receptacle.
Product Type	90 Degree 6 In PT CNTR Solid
Special Features	Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing. Large brass contacts snugly terminate on device blade terminals. Pre-stripped connector leads fasten to conductors, easier than standard pigtails. Exclusive patented feature, circuit label on back allows permanent circuit identification.



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

м	١.	_		4	c _	_ 1				c _					
ľ	۱,	-	n	111		CI		·Δr	' In	ГЛ	rr	ทว	1	n	n
	v			u	а	L - I	u	C-1	'In	W		110		w	

Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007044553
Manufacturers Part Number	PTRA6-SOL
UPC	785007044553

Taxonomies, Classifications, and Categories

Category Description	Miscellaneous residential devices
Type	PlugTail™ Connector - Right Angle

Packaging

···~g···g		
Carton	1	
Package		
Weight Per each		

Uses, Certifications, and Standards

Application Commercial	
environmental conditions Flammability: UL94 V2	
Mounting Device, Wall	
standard CULUS, UL, cULus UL498	
Temperature Rating -40° - 60° C	