

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



QBGFEP1015 Bolt On GFCB W/PCB 10KAIC 15A 30MA Trip *Eaton Corp*

1	
Catalog Number	QBGFEP1015
Manufacturer	Eaton Corp
Description	Eaton QB Gfci Circuit Breaker, Quicklag Industrial Ground Fault Thermal-Magnetic Circuit Breaker, Single-Pole, 30 Ma Trip Sensitivity, 15 A, 10 Kaic, 120V, Bolt-On Mounting
Weight per unit	0.4000 (lbs/each)
Product Category	On Circuit Breakers
Features	
dimensions	5.2000 IN X 3.3000 IN X 1.2000 IN
interrupt rating	10
Poles	1
Voltage Rating	120V
Descriptions	
Description	BOLT ON GFCB W/PCB 10KAIC 15A 30MA TRIP
extra long description	ETN QBGFEP1015 30ma EPD BREAKER
Features	Eaton has a wide selection of UL rated miniature circuit breakers for loadcenters, fuseboxes, or similar devices. Each pole provides steel frame calibration and arc chutes with 5 - 100A continuous in one-, two-, and three-pole designs. A full-range of accessories expand customization options, including various mounting and ring tung termination options.
Long Description	Eaton QB GFCI circuit breaker, Quicklag Industrial Ground Fault Thermal-Magnetic Circuit Breaker, Single-pole, 30 mA Trip Sensitivity, 15 A, 10 kAIC, 120V, Bolt-on mounting
Product Type	30MA Epd Breaker
Manufacturer Information	
Brand	Eaton
GTIN	00786679145111
Manufacturers Part Number	QBGFEP1015
UPC	786679145111
Taxonomies, Classifications, and (Categories
Category Description	Foult Consing Proglers (AFCL/CFCL)
Type	GFCI circuit breakers
Packaging	
Carton	1
Weight Per each	0.4

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

ooj ooi tiiioatioiioj aila otali	idal do
Application	Generation - Conventional Energy - Conventional
	EnergyOtherGeneration - Renewable Energy - Alternative
	EnergyDatacenters - IT Space: CI and Hyper ConvergedMarine
	Vessels and Equipment - Marine Vessels and Equipment - Other
standard	UL 943