

Specifications



Photo is representative



Eaton R5A3040U

Eaton rotary disconnect switch, 40 A, Non-fusible, Three-pole, Rotary switch, R5 Series, 600 V

General specifications

PRODUCT NAME	Eaton rotary disconnect switch
CATALOG NUMBER	R5A3040U
UPC	786685402888
PRODUCT LENGTH/DEPTH	2.57 in
PRODUCT HEIGHT	3.35 in
PRODUCT WIDTH	1.77 in
PRODUCT WEIGHT	0.5 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	CCC Marked
CERTIFICATIONS	CSA Certified EN Listed IEC Rated UL 508
CATALOG NOTES	Suitable as motor disconnect



Powering Business Worldwide

Physical Attributes

NUMBER OF POLES	Three-pole
SERIES	R5

Performance Ratings

AMPERAGE RATING	40A
VOLTAGE RATING	600 V

Miscellaneous

PRODUCT CATEGORY	Rotary Switch
------------------	---------------

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
MULTIMEDIA	Switching Devices Flex Center
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - R5A3040U

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.



Specifications



Photo is representative



Eaton R5A3040U

Eaton rotary disconnect switch, 40 A, Non-fusible, Three-pole, Rotary switch, R5 Series, 600 V

General specifications

PRODUCT NAME	Eaton rotary disconnect switch
CATALOG NUMBER	R5A3040U
UPC	786685402888
PRODUCT LENGTH/DEPTH	2.57 in
PRODUCT HEIGHT	3.35 in
PRODUCT WIDTH	1.77 in
PRODUCT WEIGHT	0.5 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	CCC Marked
CERTIFICATIONS	CSA Certified EN Listed IEC Rated UL 508
CATALOG NOTES	Suitable as motor disconnect



Powering Business Worldwide

Physical Attributes

NUMBER OF POLES	Three-pole
SERIES	R5

Performance Ratings

AMPERAGE RATING	40A
VOLTAGE RATING	600 V

Miscellaneous

PRODUCT CATEGORY	Rotary Switch
------------------	---------------

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
MULTIMEDIA	Switching Devices Flex Center
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - R5A3040U

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

