



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3520 S Sam Houston Pkwy East Suite 900  
77047-0000, TX Houston  
Phone: 281-412-7049  
Fax: 281-412-7314



## RB150125A 1-1/2" X 1-1/4" Reducing Bushing Alu

*Appleton/Oz Gedney*

Catalog Number	RB150125A
Manufacturer	Appleton/Oz Gedney
Description	Reducing Bushing, Size: 1-1/2 X 1-1/4 In, Material: Aluminum, Finish: Natural, Connection: NPT, Standard: Class I: Groups A, B, C, D, Class Ii: Groups E, F, G, Class Iii, UI 886 (1203), UI E10444, Csa C22.2 No. 25, C22.2 No. 30, Csa 065
Weight per unit	0.0800 (lbs/each)
Product Category	Aluminum

### Features

connection	NPT
Material	Aluminum

### Material, Color, and Finish

Finish	Natural
--------	---------

### Dimensions and Weight

Size	1-1/2 x 1-1/4
------	---------------

### Descriptions

Description	1-1/2" X 1-1/4" REDUCING BUSHING ALU
extra long description	APP RB150125A RDC BUSH ALUM 1-1/2TO
Long Description	Reducing Bushing, Size: 1-1/2 X 1-1/4 IN, Material: Aluminum, Finish: Natural, Connection: NPT, Standard: Class I: Groups A, B, C, D, Class II: Groups E, F, G, Class III, UL 886 (1203), UL E10444, CSA C22.2 No. 25, C22.2 No. 30, CSA 065
Product Type	RDC Bush Alum 1-1/2TO1-1/4 In
Special Features	Smooth rounded integral bushing protects conductor insulation

### Manufacturer Information

Brand	Appleton
GTIN	00781381655002
Manufacturers Part Number	RB150125A
UPC	781381655002

### Taxonomies, Classifications, and Categories

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs
Type	Reducing Bushing

### Packaging

Carton	25
Package	50
Weight Per each	0.08



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3520 S Sam Houston Pkwy East Suite 900  
77047-0000, TX Houston  
Phone: 281-412-7049  
Fax: 281-412-7314

## Uses, Certifications, and Standards

Application

For Reducing Conduit Entries To A Smaller Size In Threaded Rigid  
And IMC Conduit Systems

standard

Class I: Groups A, B, C, D, Class II: Groups E, F, G, Class III, UL 886  
(1203), UL E10444, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181