

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1315 2nd Street MAIP 74361-0000, OK Pryor Phone: 918-803-0063 Fax: 918-803-0064



Туре

RF9540NDLA Dim Aspirerf Deco MSTR All-Load Neut La *Eaton Wiring Devices*

And the second se	
Catalog Number	RF9540NDLA
Manufacturer	Eaton Wiring Devices
Description	Eaton Z-Wave Dimmer Switch, Light Almond, Single Pole, 120
	Vac, 300W Dimmable Led/CFL, 600W Incandescent, Halogen,
	Magnetic Low Voltage, Electronic Low Voltage, Dimmer Switch,
	Multi-Location, 32°F to 104°F (0°C to 40°C) 739033
Weight per unit	0.3700 (lbs/each)
Product Category	Lighting Dimmers
Features	
dimensions	1.3600 IN X 1.5000 IN X 3.8100 IN
media	Yes
Voltage Rating	120 V
Wattage	300 W (LED, CFL), 600 W (INC/HAL, ELV, MLV)
Descriptions	
Description	DIM ASPIRERF DECO MSTR ALL-LOAD NEUT LA
extra long description	EWD RF9540-NDLA Dim AspireRF Deco M
Features	Add wireless control to your lighting with Eaton's Z-Wave
	wireless collection to make your home connected and smart. This
	complete offering of lighting controls is easy to install, requires
	no special wiring and is perfect for both existing homes and new
	construction. With Z-Wave based technology you can create your
	own wireless home network to enhance security, control
	appliances, set the right mood and save energy. Select from a
	range of styles and colors to match your home's decor.
Long Description	Eaton Z-Wave dimmer switch, Light Almond, Single pole, 120 Vac
	300W Dimmable LED/CFL, 600W Incandescent, Halogen,
	Magnetic Low Voltage, Electronic Low Voltage, Dimmer switch,
Product Type	Multi-location, 32°F to 104°F (0°C to 40°C) 739033 Dim Aspirerf Deco MSTR All-Load Neut La
Special Features	RF Controls Dimmers
Manufacturer Information	
Brand	Eaton
GTIN	00032664739033
Manufacturers Part Number	RF9540-NDLA
UPC	032664739033
Taxonomies, Classifications, and C Category Description	Residential dimmers, motion sensors, controls, & photo cells

Dimmer switch



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

1315 2nd Street MAIP 74361-0000, OK Pryor Phone: 918-803-0063 Fax: 918-803-0064

Availability Status	Inactive
Packaging	
Carton	1
Package	6
Weight Per each	0.37
Uses, Certifications, and Standards	
Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities - Other
Operating Temperature	32 to 104 °F (0 to 40 °C)
standard	NOM,cULus Listed