

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Trade Size

Trade Size

PSRF326H 1"-3/4" Stainless Reducing Rushing Hygienic

RSRE326H Robroy/Stail	1 1"-3/4" Stainless Reducing Bushing Hygienic nless Steel
Catalog Number	RSRE326H
Manufacturer	Robroy/Stainless Steel
Description	Robroy Stainless Hygienic Reducing Bushings Reduce Conduit Hubs to A Smaller Size. They Are Made Of 316 Stainless Steel and Are Specially Designed For The Hygienic System and Are Provided With A Circular Conduit Entry Gasket Made Of Fda Approved Silicone At The Female Thread and An Extended Design On The Male Threads Allowing For A Sealed Connection.
Weight per unit	
Product Category	Boxes & Covers
Features	
Matarial	316
outside diameter	
Material, Color, and Finis	
Finish	Brushed
Dimensions and Weight Length	1.41
· ·	
Descriptions	1" 2/4" CTAINH FCC DEDITCHIC DUICHING LIVEIENIC
Description	1"-3/4" STAINLESS REDUCING BUSHING HYGIENIC ROB-R RE326H HYG RDC BSHG 1"-3/4" 3
extra long description Long Description	
Long Description	Robroy Stainless Hygienic Reducing Bushings reduce conduit hubs to a smaller size. They are made of 316 stainless steel and are specially designed for the hygienic system and are provided with a circular conduit entry gasket made of FDA approved silicone at the female thread and an extended design on the male threads allowing for a sealed connection.
Product Type	Hyg RDC BSHG 1"-3/4" 316 W/Cond Ent GSKT
Manufacturer Informatio	n
Brand	Robroy Stainless
GTIN	00784011010864
Manufacturers Part Num	
UPC	784011919864
Taxonomies, Classificatio	ns. and Categories
Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs
Туре	Reducing Bushings

1-1/4



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight	0.2
Weight Per each	0.2
Uses, Certifications, and Standards	
standard	UL 514B, E200413, CSA C22.2 No. 18.1-04, NSF/ANSI/3-A
	14159-1, TYPE 4X,IP69/IP69K