



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## **S11A Nylon-Ins Butted Seam STD Closed Connector** *Minnesota Mining (3M)*

|                  |                                                                                                                                                                                                                                                                                                                                                              |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number   | S11A                                                                                                                                                                                                                                                                                                                                                         |
| Manufacturer     | Minnesota Mining (3M)                                                                                                                                                                                                                                                                                                                                        |
| Description      | 3M™ Scotchlok™ Color-Coded Closed-End Connector Is An Electrical Crimp Sleeve Connector With A Copper Insert That Allows For Fast Splicing Of Copper Conductors. The Vinyl-Insulated Connector Is 600V-Rated For Building Wire and 1000V-Rated For Signs, Fixtures or Luminaires. It Withstands Temperatures Of -40 to 221 Degrees F (-40 to 105 Degrees C). |
| Weight per unit  | 1.3 (lbs/each)                                                                                                                                                                                                                                                                                                                                               |
| Product Category | Large Terminals & Connectors                                                                                                                                                                                                                                                                                                                                 |

### **Descriptions**

|                        |                                                                                                                                                                                                                                                                                                                                                              |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description            | NYLON-INS BUTTED SEAM STD CLOSED CONNECTOR                                                                                                                                                                                                                                                                                                                   |
| extra long description | 3M 7000133427 3M™ Scotchlok™ Closed                                                                                                                                                                                                                                                                                                                          |
| Features               | 3M™ Scotchlok™ Closed-End Connector is color-coded for quick and easy identification of the wire size required. It allows for quick wire insertion with a smooth, flared entry. The copper insert offers good conductivity. RoHS 2011/65/EU Compliant.                                                                                                       |
| Long Description       | 3M™ Scotchlok™ Color-Coded Closed-End Connector is an electrical crimp sleeve connector with a copper insert that allows for fast splicing of copper conductors. The vinyl-insulated connector is 600V-rated for building wire and 1000V-rated for signs, fixtures or luminaires. It withstands temperatures of -40 to 221 degrees F (-40 to 105 degrees C). |
| Product Type           | 3M™ Scotchlok™ Closed-End Connectors                                                                                                                                                                                                                                                                                                                         |

### **Manufacturer Information**

|                           |                |
|---------------------------|----------------|
| Brand                     | Scotchlok      |
| GTIN                      | 00051128589977 |
| Manufacturers Part Number | S11A           |
| UPC                       | 051128589977   |

### **Taxonomies, Classifications, and Categories**

|                      |            |
|----------------------|------------|
| Category Description | WIRE NUTS  |
| Type                 | Closed End |

### **Packaging**

|                 |       |
|-----------------|-------|
| Carton          | 100   |
| Weight Per each | 1.282 |