



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



S20GB509TRUSBA Usb Plugmold 5' Stainless Steel

Wiremold/Legrand

Catalog Number	S20GB509TRUSBA
Manufacturer	Wiremold/Legrand
Description	The Wiremold 2000 Series Raceway Offers A Selection Of Steel, Aluminum, and Nonmetallic Raceways That Provide A Versatile Solution For Many Applications. Plugmold Sections Offer Single or Alternating Circuits, In Standard or Isolated Ground Receptacles. The Scuffcoat Finish Is Scratch Resistant and Protects Against Nicks and Chips While Preventing Color From Fading.
Weight per unit	2.0 (lbs/each)
Product Category	Metallic Raceway & Accessories

Features

Enclosure Type	Stainless Steel
media	Yes
Voltage	125.0 V

Descriptions

Description	USB PLUGMOLD 5' STAINLESS STEEL
extra long description	WM S20GB509TRUSBA USB PLUGMOLD 5FT
Long Description	The Wiremold 2000 Series raceway offers a selection of steel, aluminum, and nonmetallic raceways that provide a versatile solution for many applications. Plugmold sections offer single or alternating circuits, in standard or isolated ground receptacles. The ScuffCoat finish is scratch resistant and protects against nicks and chips while preventing color from fading.
Product Type	Usb Plugmold 5FT Stainless STL
Special Features	Tamper-resistant receptacles, USB Charging, Multiple colors available, Compact design, UL5 and ADA compliant, UL and cUL listed raceway

Manufacturer Information

Brand	WIREMOLD
GTIN	00786776184457
Manufacturers Part Number	S20GB509TRUSBA
UPC	786776184457

Taxonomies, Classifications, and Categories

Category Description	Wire/Plug Strips, Surf Raceways, Power Pole, Walkerduct, & Plugmolds
Type	Plugmold

Trade Size

Amperage	15.0
----------	------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	2
Weight Per each	2.04

Uses, Certifications, and Standards

environmental conditions	Dry Interior Locations
standard	NAFTA, CULUS, ROHS, cULus Listed Multioutlet Assembly: File E15191 Guide PVGT/PVGT7