



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



S39752 60W Led Hid Adj Panels 50K Mog Base

Satco

Catalog Number	S39752
Manufacturer	Satco
Description	60 Watt Led Hid Replacement - 5000K - Mogul Extended Base - Adjustable Beam Angle - 100-277 Volts
Weight per unit	2.1 (lbs/each)
Product Category	Lighting

Features

average life	50000
Base	EX39
beam angle	120/150/260
dimmable	Non-Dimmable
lumens	8400
Material	Thermo Plastic (PBT); Steel; Aluminum
Power Factor	>0.9
Shape	ED28
surge protection	Built-in surge protection - 4KV
voltage range	277
Voltage Rating	120 to 277
Warranty	5 Year Limited - Hi-Pro
Wattage	60

Material, Color, and Finish

color rendering index (cri)	80+
color temperature	5000
Finish	Clear

Dimensions and Weight

Size	7.76
------	------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Descriptions

Description	60W LED HID ADJ PANELS 50K MOG BASE
extra long description	SATCO S39752 60W/LED/HID/MB-G3/50K/
Long Description	60 Watt LED HID Replacement - 5000K - Mogul Extended Base - Adjustable Beam Angle - 100-277 Volts
Product Type	60W/Led/Hid/MB-G3/50K/100-277V
Special Features	Warranty: 5-Years ; Location Rating: Damp ; Operating Temp: -20C (-4F) to +65C (+149F) ; Material: Aluminum / Steel / Thermo Plastic (PBT) ; Indoor Outdoor: Indoor;Outdoor ; Surge Protection: Built-in surge protection - 4KV ; Color Temp: Natural Light ; Efficacy: 140.00 LPW ; DLC Approved: False ; FCC Compliant: True ; Indoor Outdoor: Indoor;Outdoor ; Lamp Filament: LED ; ANSI Base: EX39 ; Lamp Ballast Type AB: Type B ; Amps: 0.600-0.217A ; T24 Compliant: False

Manufacturer Information

Brand	Satco
GTIN	00045923397523
Manufacturers Part Number	S39752
UPC	045923397523

Taxonomies, Classifications, and Categories

Category Description	LED SPECIALTY LAMPS & MODULES
Type	LED HID Replacements

Packaging

Carton	1
Package	6
Weight	2.05
Weight Per each	2.05

Uses, Certifications, and Standards

Application	LED
Operating Temperature	-20C (-4F) to a maximum of +65C (+149F)
standard	cULus - Certified;cULus - Classified;cULus - Listed