

STAINLESS STEEL FDX & FSX SINGLE GANG BOXES

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- Machined standard NPT threads
- Internal grounding screw included
- Manufactured with mounting feet
- No package quantity required

Certifications and Compliances:

- UL Listed 514A
- File # E307133
- Intended for installation in accordance with Article 314 of ANSI/NFPA 70, National Electrical Code (NEC)

Applications:

Used for wiring devices, such as switches and receptacles.



Part Number	Trade Size (in)	Overall Length (in)	Overall Width (in)	Depth (in)	Cubic (in)	Center Hole to Center Hole (in)	Mounting Feet Hole Diameter (in)	Weight per each (lb)
S60700FDX0	¾	6.25	4.120	2.670	25	3.250	⅝	2.56
S60700FSX0	¾	6.25	4.120	2.000	18	3.250	⅝	2.22

All dimensions are for informational purposes only *Tolerances +/- 5%



STAINLESS STEEL FDX & FSX SINGLE GANG BOXES

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- Machined standard NPT threads
- Internal grounding screw included
- Manufactured with mounting feet
- No package quantity required

Certifications and Compliances:

- UL Listed 514A
- File # E307133
- Intended for installation in accordance with Article 314 of ANSI/NFPA 70, National Electrical Code (NEC)

Applications:

Used for wiring devices, such as switches and receptacles.



Part Number	Trade Size (in)	Overall Length (in)	Overall Width (in)	Depth (in)	Cubic (in)	Center Hole to Center Hole (in)	Mounting Feet Hole Diameter (in)	Weight per each (lb)
S60700FDX0	¾	6.25	4.120	2.670	25	3.250	⅝	2.56
S60700FSX0	¾	6.25	4.120	2.000	18	3.250	⅝	2.22

All dimensions are for informational purposes only *Tolerances +/- 5%

