

Specifications



Photo is representative



Eaton S811+T30P3S

Eaton S811+ soft starter, Soft Starter 200MM 304 A Pump control with OPT Inside delta

General specifications

PRODUCT NAME	Eaton S811+ soft starter
---------------------	--------------------------

CATALOG NUMBER	S811+T30P3S
-----------------------	-------------

UPC	786685559025
------------	--------------

PRODUCT LENGTH/DEPTH	19 in
-----------------------------	-------

PRODUCT HEIGHT	12.5 in
-----------------------	---------

PRODUCT WIDTH	14.5 in
----------------------	---------

PRODUCT WEIGHT	45 lb
-----------------------	-------

COMPLIANCES	CE Marked
--------------------	-----------

CERTIFICATIONS	IEC 60947-4-2 EN 60947-4-2 UL Listed CSA Certified CSA Certified for Elevator Duty UL Recognized CSA file No. 3211-06
-----------------------	---



Powering Business Worldwide

Product specifications

AMPERAGE RATING	95-304A
SPECIAL FEATURES	30 second ramp or 450% current limit at 50°C, inside-the-delta connection, pump control and extended ramp functions
TYPE	Premium
FRAME SIZE	T
RATING	90 kW at 230 V, 160 kW at 380-400 V, 185 kW at 440 V

Resources

CATALOGS	Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1 Product Range Catalog Drives Engineering
MULTIMEDIA	Soft starter DS7 up to 200 A Soft Starter DS7 up to 32 A Soft Starter Product Family Overview
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - S811+T30P3S
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



Specifications



Photo is representative



Eaton S811+T30P3S

Eaton S811+ soft starter, Soft Starter 200MM 304 A Pump control with OPT Inside delta

General specifications

PRODUCT NAME	Eaton S811+ soft starter
---------------------	--------------------------

CATALOG NUMBER	S811+T30P3S
-----------------------	-------------

UPC	786685559025
------------	--------------

PRODUCT LENGTH/DEPTH	19 in
-----------------------------	-------

PRODUCT HEIGHT	12.5 in
-----------------------	---------

PRODUCT WIDTH	14.5 in
----------------------	---------

PRODUCT WEIGHT	45 lb
-----------------------	-------

COMPLIANCES	CE Marked
--------------------	-----------

CERTIFICATIONS	IEC 60947-4-2 EN 60947-4-2 UL Listed CSA Certified CSA Certified for Elevator Duty UL Recognized CSA file No. 3211-06
-----------------------	---



Powering Business Worldwide

Product specifications

AMPERAGE RATING	95-304A
SPECIAL FEATURES	30 second ramp or 450% current limit at 50°C, inside-the-delta connection, pump control and extended ramp functions
TYPE	Premium
FRAME SIZE	T
RATING	90 kW at 230 V, 160 kW at 380-400 V, 185 kW at 440 V

Resources

CATALOGS	Solid-State Motor Control, Reduced Voltage Motor Starters, Volume 6, Tab 1 Product Range Catalog Drives Engineering
MULTIMEDIA	Soft starter DS7 up to 200 A Soft Starter DS7 up to 32 A Soft Starter Product Family Overview
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - S811+T30P3S
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

