



SB-1



SB-1H



SB-2



SB-3



SB-4



LVP-2



SB-2 with LVP installed

SLIDERBOX® Adjustable Boxes

| Cu. In. Volume | Catalog Number | Component Description                                                                                                                                                                                                             | Exterior Dimensions |         |        | UPC# 85339 | Std. Pkg. Qty. | Std. Wt. (lb.) |
|----------------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------|--------|------------|----------------|----------------|
|                |                |                                                                                                                                                                                                                                   | D                   | W       | H      |            |                |                |
| 23.0           | SB-1           | Single gang adjustable outlet box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, ½" knockout                                                                                          | 3-9/16              | 2-5/16  | 3-¾    | 94500      | 48             | 14             |
| 23.0           | SB-1H          | Single gang adjustable outlet box, <b>horizontal mount</b> , internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, ½" knockout                                                                | 3-9/16              | 3-¾     | 2-5/16 | 94503      | 12             | 4              |
| 42.0           | SB-2           | Two-gang adjustable outlet box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts                                                               | 3-9/16              | 4       | 3-¾    | 94501      | 24             | 9              |
| 61.0           | SB-3           | Three-gang adjustable outlet box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts                                                             | 3-9/16              | 5-13/16 | 3-¾    | 94502      | 6              | 3              |
| 74.8           | SB-4           | Four-gang adjustable outlet box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts<br><b>*NOTE:</b> Not UL® classified for fire resistive walls | 3-9/16              | 7-5/8   | 3-¾    | 94504      | 6              | 4              |

Low Voltage Partition

| Catalog Number | Component Description                                        | UPC# 85339 | Std. Pkg. Qty. | Std. Wt. (lb.) |
|----------------|--------------------------------------------------------------|------------|----------------|----------------|
| LVP-2          | Low voltage divider plate for use with SB-2, SB-3, and SB-4. | 80005      | 50*            | 3              |

\* Consists of ten (10) packages of five (5) pieces each.



SB-CB



SB-CBG




SB-CBFR




Outlet Box  
UL File No. E30594

SLIDERBOX® 4" Dia.

| Cu. In. Volume | Catalog Number | Component Description                                                                                                                                                                                                     | Exterior Dim. |   | Fan Rating | Fixture Rating | UPC# 85339 | Std. Pkg. Qty. | Std. Wt. (lb.) |
|----------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---|------------|----------------|------------|----------------|----------------|
|                |                |                                                                                                                                                                                                                           | D             | W |            |                |            |                |                |
| 25.0           | SB-CB          | 4" diameter adjustable ceiling box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts                                                   | 2-¾           | 4 | —          | 50 lb.         | 94505      | 12             | 3              |
| 25.0           | SB-CBG         | 4" diameter adjustable ceiling box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, ground strap, molded-in Speed Klamps™, two ½" knockouts                                     | 2-¾           | 4 | —          | 50 lb.         | 94507      | 12             | 4              |
| 25.0           | SB-CBFR        | 4" diameter adjustable fan & fixture support, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts, paddle fan mounting bracket and screws | 2-¾           | 4 | 70 lb.     | 90 lb.         | 94506      | 12             | 10             |



Slider plate in full forward position sets box for 1/2" drywall.



Slider plate retracted sets box in fully adjusted forward position for maximum wall substrate thickness of 1-3/8".





SB-1



SB-1H



SB-2



SB-3



SB-4



LVP-2



SB-2 with LVP installed

SLIDERBOX® Adjustable Boxes

| Cu. In. Volume | Catalog Number | Component Description                                                                                                                                                                                                             | Exterior Dimensions |         |        | UPC# 85339 | Std. Pkg. Qty. | Std. Wt. (lb.) |
|----------------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------|--------|------------|----------------|----------------|
|                |                |                                                                                                                                                                                                                                   | D                   | W       | H      |            |                |                |
| 23.0           | SB-1           | Single gang adjustable outlet box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, ½" knockout                                                                                          | 3-9/16              | 2-5/16  | 3-¾    | 94500      | 48             | 14             |
| 23.0           | SB-1H          | Single gang adjustable outlet box, <b>horizontal mount</b> , internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, ½" knockout                                                                | 3-9/16              | 3-¾     | 2-5/16 | 94503      | 12             | 4              |
| 42.0           | SB-2           | Two-gang adjustable outlet box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts                                                               | 3-9/16              | 4       | 3-¾    | 94501      | 24             | 9              |
| 61.0           | SB-3           | Three-gang adjustable outlet box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts                                                             | 3-9/16              | 5-13/16 | 3-¾    | 94502      | 6              | 3              |
| 74.8           | SB-4           | Four-gang adjustable outlet box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts<br><b>*NOTE:</b> Not UL® classified for fire resistive walls | 3-9/16              | 7-5/8   | 3-¾    | 94504      | 6              | 4              |

Low Voltage Partition

| Catalog Number | Component Description                                        | UPC# 85339 | Std. Pkg. Qty. | Std. Wt. (lb.) |
|----------------|--------------------------------------------------------------|------------|----------------|----------------|
| LVP-2          | Low voltage divider plate for use with SB-2, SB-3, and SB-4. | 80005      | 50*            | 3              |

\* Consists of ten (10) packages of five (5) pieces each.



SB-CB



SB-CBG



SB-CBFR




Outlet Box


UL File No. E30594

SLIDERBOX® 4" Dia.

| Cu. In. Volume | Catalog Number | Component Description                                                                                                                                                                                                     | Exterior Dim. |   | Fan Rating | Fixture Rating | UPC# 85339 | Std. Pkg. Qty. | Std. Wt. (lb.) |
|----------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---|------------|----------------|------------|----------------|----------------|
|                |                |                                                                                                                                                                                                                           | D             | W |            |                |            |                |                |
| 25.0           | SB-CB          | 4" diameter adjustable ceiling box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts                                                   | 2-¾           | 4 | —          | 50 lb.         | 94505      | 12             | 3              |
| 25.0           | SB-CBG         | 4" diameter adjustable ceiling box, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, ground strap, molded-in Speed Klamps™, two ½" knockouts                                     | 2-¾           | 4 | —          | 50 lb.         | 94507      | 12             | 4              |
| 25.0           | SB-CBFR        | 4" diameter adjustable fan & fixture support, internal stud screws for use in wood or steel non-load-bearing studs 25 gauge or lighter, molded-in Speed Klamps™, two ½" knockouts, paddle fan mounting bracket and screws | 2-¾           | 4 | 70 lb.     | 90 lb.         | 94506      | 12             | 10             |



Slider plate in full forward position sets box for 1/2" drywall.



Slider plate retracted sets box in fully adjusted forward position for maximum wall substrate thickness of 1-3/8".



SLIDERBOX® can be used in New Work or Old Work/Manufactured Housing Applications

All dimensions are in inches unless otherwise noted.



Flush-Device Box

UL File No. E30594