



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

12555 Harris Branch Pkwy Suite 105
78653-0000, TX Manor
Phone: 512-339-8750
Fax: 512-339-6732



SBS1 600V 1A 1 3/8X13/32 Fuse *Mersen Fuses*

Catalog Number	SBS1
Manufacturer	Mersen Fuses
Description	Fuse SBS - Midget - Fast-Acting 600VAC 1A Ferrule
Weight per unit	0.0150 (lbs/each)
Product Category	Small Dimension Fuses

Features

AC Voltage Rating	600
amperage rating	1
class	Midget
connection	Ferrule
Fuse Class	Midget
interrupt rating	100
Voltage Rating	600

Material, Color, and Finish

Body Material	GMG
---------------	-----

Dimensions and Weight

Size	1.38 x 0.41
------	-------------

Descriptions

Description	600V 1A 1 3/8X13/32 FUSE
extra long description	Mersen SBS1 Fuse SBS - Midget - Fas
Features	SBS midget fast-acting fuses were developed in response to the industry's demand for smaller equipment and components. They are the only fuses in their size with a full 600VAC rating for all ampere ratings by UL Standard 248-14 and CSA No. 59.2, and are the only fuses of this size with an interrupting rating of 100kA RMS, compared to 10kA on other brands.
Long Description	Fuse SBS - Midget - Fast-Acting 600VAC 1A Ferrule
Product Type	Sicherungseinsatz SBS – Miniatur – Flink 600VAC 1A Kapselsic
Short Description	600V 1A 1 3/8x13/32 FUSE
Special Features	Small unique physical size for maximum design flexibility and noninterchangeability with other fuse classes Fiberglass body provides dimensional stability in harsh industrial environments Can be used with UltraSafe™ fuse holder 1 3/8" x 13/32" dimensions



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

12555 Harris Branch Pkwy Suite 105
78653-0000, TX Manor
Phone: 512-339-8750
Fax: 512-339-6732

Manufacturer Information

Brand	Mersen
GTIN	00782001907730
Manufacturers Part Number	SBS1
UPC	782001907730

Taxonomies, Classifications, and Categories

Category Description	MIDGET FUSES
Type	Midget Fuses

Packaging

Carton	1
Package	10
Weight Per each	0.015

Uses, Certifications, and Standards

Application	Control circuits Lighting ballasts Meter circuits Electronic circuits General purpose protection
Mounting standard	Clip UL listed to standard 248-14 File E33925 CSA Certified to Standard C22.2 No. 248.14