

Kellems® Wire Management Products
Straight Male Cord Connectors
Cord Connectors

HUBBELL

Features

- Aluminum cord connector provides durable performance
- Knurled finish makes them easy to handle and maintain UL listing by hand tighteningUL listing by hand tightening
- Lightweight design

Ordering Information

Description	Color Code	UPC	Catalog Number
Cord Connectors, Straight Male, Aluminum	Blue	783585200231	SHC1023

Listings

UL Listed
CSA Certified

Specifications

Material	Aluminum
Form Size	F2
NPT Hub Size	1/2 Inch
Cord Diameter Range Inches (mm)	.38"-.50" (9.7-12.7)

Performance

Environmental

Hazardous Locations	Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC
Operating Temperatures	-30°F to +225°F (-34°C to +107°C)



Online Resources

eCatalog

Kellems® Wire Management Products
Straight Male Cord Connectors
Cord Connectors

HUBBELL

Features

- Aluminum cord connector provides durable performance
- Knurled finish makes them easy to handle and maintain UL listing by hand tighteningUL listing by hand tightening
- Lightweight design

Ordering Information

Description Cord Connectors, Straight Male, Aluminum	Color Code Blue	UPC 783585200231	Catalog Number SHC1023
---	--------------------	---------------------	---------------------------

Listings

UL Listed
CSA Certified

Specifications

Material	Aluminum
Form Size	F2
NPT Hub Size	1/2 Inch
Cord Diameter Range Inches (mm)	.38"-.50" (9.7-12.7)

Performance

Environmental

Hazardous Locations	Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC
Operating Temperatures	-30°F to +225°F (-34°C to +107°C)



Online Resources

eCatalog