



SPM26L #2 SVC Post Conn

Nsi Industries

Catalog Number	SPM26L
Manufacturer	Nsi Industries
Description	Service Post Connector - Two Wire Type 4-1/0 Awg Service Post Connectors Is Used For Connecting One or Two Conductors. Made From High Copper Content Hard-Drawn Rod. Lay-In Feature Makes Them Excellent For Continuous Loop Grounding and Bonding. Used to Ground to Bar or Plate. Suitable For Direct Burial In Earth or Concrete.
Weight per unit	0.3600 (lbs/each)
Product Category	Large Terminals & Connectors

Features

Number of Conductors	2
Poles	1
Voltage Rating	600 V
Warranty	1 YEAR
Wire Size	4 SOL - 1/0 STR
Wire Type	Class A & B

Material, Color, and Finish

Color	Copper
Finish	COPPER
Housing Material	Copper

Dimensions and Weight

Size	Stud=1/2 x 13-1 1/4 - Hex Nut=3/4 x 16
------	--



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

12555 Harris Branch Pkwy Suite 105
78653-0000, TX Manor
Phone: 512-339-8750
Fax: 512-339-6732

Descriptions

Description	#2 SVC POST CONN
extra long description	NSI SPM-26L Service Post Two Wire 4
Features	Service Post Connector - Two Wire Type 4-1/0 AWG Service Post Connectors is used for connecting one or two conductors. Made from high copper content hard-drawn rod. Lay-in feature makes them excellent for continuous loop grounding and bonding. Used to ground to bar or plate. Suitable for direct burial in earth or concrete.
Long Description	Service Post Connector - Two Wire Type 4-1/0 AWG Service Post Connectors is used for connecting one or two conductors. Made from high copper content hard-drawn rod. Lay-in feature makes them excellent for continuous loop grounding and bonding. Used to ground to bar or plate. Suitable for direct burial in earth or concrete.
Product Type	Service Post Two Wire 4-1/0 Awg
Special Features	4 SOL-1/0 STR - 12 Pack

Manufacturer Information

Brand	NSI
GTIN	00662381021151
Manufacturers Part Number	SPM-26L
UPC	662381021151

Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
Type	Service Post Connectors

Packaging

Carton	1
Package	12
Weight Per each	0.36

Uses, Certifications, and Standards

Application	Wire Termination
environmental conditions	90 C
standard	UL486B